



black pushbutton Ø 22 - spring return - 1 NO - ATEX

XB4BP21EX

Main

Range of product	Harmony XB4	
Product or component type	Complete push-button	
Device short name	nort name XB4	
Bezel material	Chromium plated metal	
Fixing collar material	Zamak	
Head type	Standard	
Mounting diameter	22 mm	
Sale per indivisible quantity	1	
Dust zone	Zone 21 - 22	
Type of operator	spring return	
Operator profile	Black projecting	
Operator additional information	Booted (clear silicon)	
Contacts type and composition	1 NO	

Complementary

oompromontar y		
Resistance to high pressure washer	7000000 Pa at 55 °C, distance : 0.1 m	
Device mounting	Fixing hole - diameter: 22.5 mm 22.3 +0.4/0 conforming to IEC 60947-1	
Fixing center	>= 30 x 40 mm (support panel)	
Embedding depth	43 mm	
Marking	Ex tb IIIC	
Shape of signaling unit head	Round	
Contact operation	Slow-break	
Positive opening	Without	
Operating travel	4.3 mm (total travel)	
Operating force	3.8 N NO changing electrical state	
Mechanical durability	nical durability 5000000 cycles	
onnections - terminals Screw clamp terminals, 1 x 0.222 x 2.5 mm² without cable end conforming 60947-1		
Tightening torque	0.81.2 N.m conforming to IEC 60947-1	
Shape of screw head	Cross compatible with pozidriv No 1 screwdriver Slotted compatible with flat \emptyset 4 mm screwdriver Slotted compatible with flat \emptyset 5.5 mm screwdriver	

Contacts material	Silver alloy (Ag/Ni)	
Short-circuit protection	10 A cartridge fuse type gG conforming to IEC 60947-5-1	
[Ith] conventional free air thermal current	10 A conforming to IEC 60947-5-1	
[Ui] rated insulation voltage	600 V (pollution degree 3) conforming to IEC 60947-1	
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-1	
[le] rated operational current	6 A at 120 V, AC-15, A600 conforming to IEC 60947-5-1 0.1 A at 600 V, DC-13, Q600 conforming to IEC 60947-5-1 0.27 A at 250 V, DC-13, Q600 conforming to IEC 60947-5-1 0.55 A at 125 V, DC-13, Q600 conforming to IEC 60947-5-1 1.2 A at 600 V, AC-15, A600 conforming to IEC 60947-5-1	
Electrical durability	1000000 cycles AC-15, 3 A at 120 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1: appendix C 1000000 cycles AC-15, 4 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1: appendix C 1000000 cycles DC-13, 0.2 A at 110 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1: appendix C 1000000 cycles DC-13, 0.5 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IEC 60947-5-1: appendix C	
Electrical reliability	Λ < 10exp(-8) at 17 V, 5 mA in clean environment conforming to IEC 60947-5-4	

Environment

Protective treatment	TH	
Ambient air temperature for storage	-4070 °C	
Ambient air temperature for operation	-4070 °C	
Overvoltage category	I conforming to IEC 60536	
IP degree of protection	e of protection IP67	
NEMA degree of protection NEMA 4X		
IK degree of protection IK03 conforming to IEC 50102		
Standards	EN 50281-1-1 IEC 61241-0 IEC 61241-1 CSA C22.2 No 213	
Directives	94/9/EC - ATEX directive	
Product certifications	cations INERIS 04ATEX9004U GL	
Vibration resistance	resistance 5 gn (f= 2500 Hz) conforming to IEC 60068-2-6	
Shock resistance	50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.000 cm
Package 1 Width	14.000 cm
Package 1 Length	20.000 cm
Package 1 Weight	96.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	20

Package 2 Height	15.000 cm	
Package 2 Width	30.000 cm	
Package 2 Length	40.000 cm	
Package 2 Weight	2.196 ka	

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance


⊘	Reach Free Of Svhc	
⊘	Toxic Heavy Metal Free	
⊘	Mercury Free	
②	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

Dimensions Drawings

Pushbutton



e: support thickness: 1 to 6 mm / 0.04 to 0.24 in.


XB4BP21EX


Mounting and Clearance

Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)

Connection by Screw Clamp Terminals or Plug-in Connectors or on Printed Circuit Board

Connection by Faston Connectors





- (1) Diameter on finished panel or support
- (2) 40 mm min. / 1.57 in. min.
- (3) 30 mm min. / 1.18 in. min.
- (4) Ø 22.5 mm / 0.89 in. recommended (Ø 22.3 mm $_0^{+0.4}$ / 0.88 in. $_0^{+0.016}$)
- (5) 45 mm min. / 1.78 in. min.
- (6) 32 mm min. / 1.26 in. min.

Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features

Technical Benefits

Harmony XB4



Image of product / Alternate images

Alternative









Product datasheet





Contact: +971507924960

Email: sales@industrytechstore.com

