

Clamp

Insulation

DMMs

Detectors

Earth

Power  
qualityPower  
consumption

Battery

PV

Logger

LAN

Signal

Lux

Temperature

Sound

## HiTESTER 3030-10



CAT III 600 V

CARRYING CASE 9390

Order code **3030-10**

### Accessories



- TEST LEAD L9207-30
- CARRYING CASE 9390
- R6P manganese battery x2
- Spare fuse
- Instruction manual

L9207-30



|                        |                        |                                                                                          |
|------------------------|------------------------|------------------------------------------------------------------------------------------|
| Measurement parameters | DC Voltage             | 0.3 V/3 V/12 V/30 V/120 V/300 V/600 V<br>Accuracy: $\pm 2.5\%$ of f.s. reading           |
|                        | AC Voltage             | 12 V/ 30 V/120 V/300 V/600 V<br>Accuracy: $\pm 2.5\%$ of f.s. reading, (12V: $\pm 4\%$ ) |
|                        | DC Current             | 60 $\mu$ A/30 mA/300 mA<br>Accuracy: $\pm 3\%$ of f.s. reading                           |
|                        | Resistance             | 0 to 3k $\Omega$ , Rx1/ Rx10/ Rx100/ Rx1k<br>Accuracy: $\pm 3\%$ of scale length         |
|                        | Battery check          | 0.9 to 1.8 V<br>Accuracy: $\pm 6\%$ of f.s. reading                                      |
| Other                  | Operating temperature  | 0°C to 40°C (non-condensating)                                                           |
|                        | Storage temperature    | -10°C to 50°C (non-condensating)                                                         |
|                        | Power supply           | R6P manganese battery x2                                                                 |
|                        | Dimensions (W x H x D) | 95 x 141 x 39 mm (3.74 x 5.55 x 1.54 in)                                                 |
|                        | Weight                 | 280 g (9.9 oz)                                                                           |

CE

## CARD HiTESTER 3244-60

Cord length  
46cm (1.51 ft)

CAT III 300V, CAT II 600V

CARRYING CASE  
C0204Order code **3244-60**

### Accessories

- CARRYING CASE C0204
- Sleeves (Red, Black @ 1 each)
- CR2032 coin type battery x1
- Instruction manual



|                        |                        |                                                                                                                                                         |
|------------------------|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Measurement parameters | DC Voltage             | 420.0 mV/ 4.200 V/ 42.00 V/ 420.0 V/ 500 V<br>Accuracy: $\pm 0.7\%$ rdg $\pm 4$ dgt.                                                                    |
|                        | AC Voltage             | 4.200 V/ 42.00 V/ 420.0 V/ 500 V<br>Accuracy: $\pm 2.3\%$ rdg $\pm 8$ dgt.                                                                              |
|                        | Resistance             | 420.0 $\Omega$ / 4.200 k $\Omega$ / 42.00 k $\Omega$ / 420.0 k $\Omega$ / 4.200 M $\Omega$ / 42.00 M $\Omega$<br>Accuracy: $\pm 2.0\%$ rdg $\pm 4$ dgt. |
|                        | Continuity check       | Detection level: 50 $\Omega$ $\pm 40$ $\Omega$ or less                                                                                                  |
|                        | Operating temperature  | 0°C to 40°C (non-condensating)                                                                                                                          |
| Other                  | Storage temperature    | -20°C to 60°C (non-condensating)                                                                                                                        |
|                        | Power supply           | CR2032 coin type battery x1                                                                                                                             |
|                        | Dimensions (W x H x D) | 55 x 109 x 9.5 mm (2.17 x 4.29 x 0.37 in)                                                                                                               |
|                        | Weight                 | 60 g (2.1 oz)                                                                                                                                           |

Not CE marked

## PENCIL HiTESTER 3246-60

Cord length  
80 cm (2.62 ft)

CAT IV 300 V, CAT III 600 V

Test lead fits neatly  
into back of instrument

### Accessories

- Sleeves (Red, Black @ 1 each)
- CR2032 coin type battery x1
- Instruction manual

Order code **3246-60**

|                        |                        |                                                                                                                                                    |
|------------------------|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Measurement parameters | DC Voltage             | 420.0 mV/4.200 V/42.00 V/420.0 V/600 V<br>Accuracy: $\pm 1.3\%$ rdg $\pm 4$ dgt.                                                                   |
|                        | AC Voltage             | 4.200 V/42.00 V/420.0 V/600 V<br>Accuracy: $\pm 2.3\%$ rdg $\pm 8$ dgt.                                                                            |
|                        | Resistance             | 420.0 $\Omega$ /4.200 k $\Omega$ /42.00 k $\Omega$ /420.0 k $\Omega$ /4.200 M $\Omega$ /42.00 M $\Omega$<br>Accuracy: $\pm 2.0\%$ rdg $\pm 4$ dgt. |
|                        | Continuity check       | Detection level: 50 $\Omega$ $\pm 40$ $\Omega$ or less                                                                                             |
|                        | Diode check            | Judges the right direction only,<br>Open terminal voltage 3.4 V or less                                                                            |
| Other                  | Operating temperature  | 0°C to 40°C (non-condensating)                                                                                                                     |
|                        | Storage temperature    | -20°C to 60°C (non-condensating)                                                                                                                   |
|                        | Power supply           | CR2032 coin type battery x1                                                                                                                        |
|                        | Dimensions (W x H x D) | 30 x 182 x 26.5 mm (1.18 x 7.17 x 1.04 in)                                                                                                         |
|                        | Weight                 | 80 g (2.8 oz)                                                                                                                                      |