


SOL series


Solar Rechargeable LED Flashing Signal Lights



- Applicable in road construction sites with a limited power supply
- Applicable on vehicles that require a warning light at night
- Can be used to display vehicle position in dark residential parking areas



S80SOL



- Sun Switch**
Automatically turns on the light when darkness is detected.
Factory default is set to OFF.
- Power Switch**
ON/OFF power switch that prevents discharge prior to use.
Factory default is set to OFF.

SOL solar light model does not require external power supply or wiring!

Features High Energy Efficiency and Longevity

SOL Solar light models can be used in environmental conditions where power supply is limited or wiring is difficult.



Features High Energy Efficiency and Longevity

Qlight's solar rechargeable signal lights have a special design that mounts the solar panels inside a structure that minimizes adverse effects such as dust and moisture. This improves the efficiency and extends the lifetime of the product.



High-tide maritime surveillance systems



Low-speed night vehicle operation



Common Specifications(S80SOL/ S100SOL/ S125SOL)

- Solar rechargeable LED flashing signal light that does not require an external power supply or wiring
- Built-in Darkness Detection System that automatically begins to operate when darkness is detected
- Fully enclosed structure that can withstand storm and severe dust environments (IP54)
- Prevents discharge using a built-in power switch
- Flashing Rate : 60-80 flashes/min
- Materials : Lens-PC, Body-ABS, Reflector-Heat resistant ABS
- Ambient operating temperature : -25°C to +50°C
- Protection rating : IP54
- Certificates : CE Compliant



S80SOL Ø80mm Solar Rechargeable LED Flashing Signal Light


- 80mm Compact model
- A single charge (8 hours) serves up to 30 hours of continuous operation

| Model number | Battery Voltage | Battery Capacity | Continuous operating time with no charge | Certificates | Weight | Color Options |
|--------------|-----------------|------------------|--|--------------|--------|--|
| S80SOL | 2.4V | 0.700Ah | 30Hr | CE | 0.27kg | <ul style="list-style-type: none"> • R-Red • A-Amber |



Technical Diagram

(Units : mm)



SOL series

Solar Rechargeable LED Flashing Signal Lights



S100SOL



S125SOL



S100SOL Ø100mm Solar Rechargeable LED Flashing Signal Light


- Ø100mm model for general purpose
- 40 hours operation continuous by 1 time recharge(8 hours)

| Model number | Battery Voltage | Battery Capacity | Continuous operating time with no charge | Certificates | Weight | Color Options |
|--------------|-----------------|------------------|--|--------------|--------|--|
| S100SOL | 2.4V | 0.700Ah | 40Hr | CE | 0.41kg | <ul style="list-style-type: none"> • R-Red • A-Amber |



Technical Diagram

(Units : mm)



S125SOL Ø125mm Solar Rechargeable LED Flashing Signal Light


- Ø125mm standard item
- 50 hours of continuous operation from 1 time recharge(8 hours)

| Model number | Battery Voltage | Battery Capacity | Continuous operating time with no charge | Certificates | Weight | Color Options |
|--------------|-----------------|------------------|--|--------------|--------|--|
| S125SOL | 2.4V | 0.700Ah | 50Hr | CE | 0.51kg | <ul style="list-style-type: none"> • R-Red • A-Amber |



Technical Diagram

(Units : mm)



Ordering Specification

S80SOL

R

[Model number]

[Color]

- S80SOL
- S100SOL
- S125SOL

- R-Red
- A-Amber




Accessories

- Magnetic mounting bracket
- Wall mount bracket options : Bracket structure allows for threading through the bracket hole or into the wall mount

- S80SOL

- S100SOL/ S125SOL



Wall Mount Bracket
TWS80

Wall Mount Bracket
TWA80

Wall Mount Bracket
SWP125

Wall Mount Bracket
SWM125