

RECHARGEABLE

INTRINSICALLY SAFE DUAL-LIGHT™ FLASHLIGHT

XPR-5542GMX

NIGHTSTICK®
Life Depends on Light™



DUAL-LIGHT™

275-lumen Dual-Light™ provides simultaneous **flashlight and floodlight** operation

**IP-X7
WATER
PROOF**

**INTEGRATED
HEAVY-DUTY
MAGNET**



Large, textured buttons that are **easy-to-use with gloves**



Durable polymer body is **impact & chemical resistant**



Non-conductive body designed for hazardous environments



Powerful base magnet allows "hands-free" use

400 LUMENS



DUAL-LIGHT™ FLASHLIGHT

RECHARGEABLE

ITEM NUMBER/UPC

XPR-5542GMX - 017398806008

CERTIFICATIONS

- cULus
- ATEX
- IECEX
- Kosha
- CE
- BC

CASE MATERIAL

- ABS Polymer

LUMENS/RUNTIME

SPOTLIGHT

- HIGH: 400 lumens, 10 hrs runtime

FLOODLIGHT

- HIGH: 225 lumens, 11 hrs runtime

DUAL-LIGHT

- 275 lumens, 10 hrs runtime

CANDELA

- HIGH: 11571

BEAM DISTANCE

- HIGH: 215m

WATER RATING

- IP-67 (dust-proof/waterproof)

DROP RATING

- 2m

DIMENSIONS

- LENGTH: 9.5 in (241 mm)
- BARREL DIAMETER: 1.2 in (30 mm)
- BEZEL DIAMETER: 1.6 in (40 mm)
- WEIGHT: 10.9 oz (309 g)

BATTERY

- Integrated li-ion battery

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Light with li-ion rechargeable battery
- Snap-In rapid charger
- AC/DC power supplies
- Anti-roll ring
- Instruction manual

FL1 STANDARD	FLASH HIGH	FLASH LOW	DUAL-LIGHT
	400 LUMENS	80 LUMENS	275 LUMENS
	10h	41h	10h
	215m		
	11571cd		
	2m		
	1m		

Bayco Products, Inc. Wylie, TX 75098 XPR-5542 Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS UL listed for use with Bayco Li-ion Battery Pack 5500-BATT E 467756 ID 5012927 INTRINSICALLY SAFE SECURITE INTRINSEQUE	 2575 ZZ-AVABO-0248X US Patent 9,713,217 MFG MM-YY	CLASS I DIV 1 GRPS A-D T4 CLASS II & III DIV 1 GRPS E-G CLASS I ZONE 0 GRP IIC T4 CLASS II ZONE 20 IIC T135°C Ex ia IIC T4 Gb Ex ia IIC T4 Gb DEMKO 16 ATEX 1815 IECEX UL 16.0188 -20°C ≤ Tamb ≤ +40°C 3.7V/Cell 5500-BATT U _n = 4.75V SEE INSTRUCTION MANUAL VOIR MANUEL
--	--	--

--	--	--	--	--	--	--