



NT 75/2 AP ME TC

High-performance, dual-motor wet/dry vacuum cleaner for professional use. Effective air-blast cleaning of the flat pleated filter maintains virtually constant cleaning power.



Order no. 1.667-292.0

- Semi-automatic filter cleaning
- Tilting chassis
- Flat pleated filter (dust class M)

Technical data		
EAN code		4039784727298
Supply voltage	Ph / V / Hz	1 / 220 - 240 / 50 - 60
Air flow	l/s	2 × 74
Vacuum	mbar / kPa	254 / 25.4
Container content	l	75
Container material		Stainless steel
Rated input power	W	max. 2760
Standard nominal width		ID 40
Cable length	m	10
Sound pressure level	dB(A)	73
Colour		silver
Weight without accessories	kg	26
Dimensions (L × W × H)	mm	700 × 505 × 995

Equipment		
Suction hose	m	4
Bend		Plastic
Suction tube	Piece(s) × mm	2 × 550 / Stainless steel
Filter bag	Piece(s)	1 / Paper
Wet/dry floor nozzle	mm	360
Crevice nozzle		■
Drain hose (oil-resistant)		■
Automatic cut-out features at max. filling quality		■
Flat pleated filter		Paper
Tilting chassis		■
Filter cleaning		Semi-automatic filter cleaning Ap
Sturdy bumper		■
Push handle		■
Protection class		II
Stop swivel castor		■
■ included in the scope of supply.		



On-board storage

- The large on-board storage space on the casing head ensures that tools and accessories are always stored and close to hand.



Integrated drain hose

- Easily accessible drain hose for convenient liquid disposal.



Semi-automatic filter cleaning

- Semi-automatic filter cleaning effectively ensures constant high suction power.

ACCESSORIES FOR NT 75/2 AP ME TC

1.667-292.0



		Order no.	Description	
FLAT PLEATED FILTER, STANDARD, BIA C OR UP TO DUST CLASS M				
Flat pleated filter, paper				
Flat pleated filter, paper	1	6.904-283.0	Paper flat pleated filter (BIA-(U,S,G,C) dust class M) suitable for NT 65/2 Eco, NT 65/2 Eco Tc, NT 65/2 Eco Me.	■
Flat pleated filter, PES				
Flat pleated filter, PES	2	6.904-284.0	Flat filter (PES) - BIA-(U,S,G,C) dust class M: rotproof polyester fleece, ideal for wet use and abrasives. Standard for NT 72/2 Eco Tc.	□
Flat pleated filter, PTFE				
Flat pleated filter, PTFE	3	6.907-449.0	Polyester fleece with PTFE coating, dust class M, for Tact² vacuum cleaners. Particularly suitable for very adhesive materials.	□
BENDS				
Bend, plastic				
Bend, NT, DN 40, plastic, clip 2.0 at hose end, cone at accessory end	4	2.889-171.0	DN 40 plastic bend for wet and dry vacuum cleaners. Equipped with a clip 2.0 connection at the hose end and a cone connection at the accessory end.	■
Bend with air-flow regulator, T, DN 35, plastic, antistatic, clip 2.0 at hose end, cone at accessory end	5	2.889-148.0	Antistatic, ergonomic bends with air-flow regulator in size DN 35 for dry vacuum cleaners. Equipped with a clip 2.0 connection at the hose end and a cone connection at the accessory end.	□
Bend, NT, DN 35, plastic, clip 1.0 at hose end, cone at accessory end	6	5.031-718.0	DN 35 plastic bend for wet and dry vacuum cleaners. Equipped with a clip 1.0 connection at the hose end and a cone connection at the accessory end.	□
Bend, NT, DN 35, plastic, electrically conductive, clip 1.0 at hose end, cone at accessory end	7	5.031-939.0	Electrically conductive DN 35 plastic bend for wet and dry vacuum cleaners. Equipped with a clip 1.0 connection at the hose end and a cone connection at the accessory end.	□
Bend, NT, DN 40, plastic, electrically conductive, clip 1.0 at hose end, cone at accessory end	8	5.032-427.0	Electrically conductive DN 40 plastic bend for wet and dry vacuum cleaners. Equipped with a clip 1.0 connection at the hose end and a cone connection at the accessory end.	□
Bend, other				
Bend, NT, DN 35, chrome-plated metal, cone at hose end, cone at accessory end	9	6.900-519.0	DN 35 chrome-plated metal bend for wet and dry vacuum cleaners by Kärcher. The bend has a cone connection at both the hose end and the accessory end.	□
Bend, NT, DN 35, stainless steel, cone at hose end, cone at accessory end	10	6.903-141.0	Robust DN 35 stainless steel bend for wet and dry vacuum cleaners by Kärcher. The bend has a cone connection at both the hose end and the accessory end.	□
Bend, NT, DN 40, chrome-plated metal, cone at hose end, cone at accessory end	11	6.900-276.0	DN 40 chrome-plated metal bend for wet and dry vacuum cleaners by Kärcher. The robust bend has a cone connection at both the hose end and the accessory end.	□
Bend, NT, DN 40, stainless steel, cone at hose end, cone at accessory end	12	6.902-079.0	Robust DN 40 stainless steel bend for wet and dry vacuum cleaners by Kärcher. The bend has a cone connection at both the hose end and the accessory end.	□
SUCTION NOZZLES				
Floor nozzles				
Wet/dry floor nozzle, advanced plastic, DN 40, width 360 mm	13	2.889-153.0	360 mm wide wet and dry floor nozzle with easy-to-change inserts, squeegees.	■
Wet and dry floor nozzle, aluminium, DN 40	14	6.903-018.0	All-purpose aluminium nozzle with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	□

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR NT 75/2 AP ME TC

1.667-292.0



		Order no.	Description	
SUCTION NOZZLES				
Floor nozzles				
Wet/dry floor nozzle, aluminium, DN 40	15	6.906-383.0	All-purpose aluminium nozzle (DN 40) with 450 mm working width. With height-adjustable side rollers, brush strips (6.903-065.0) and oil-resistant squeegees (6.906-146.0). Only for NT vacuum cleaners.	☐
Wet/dry floor nozzle, aluminium, DN 35	16	6.906-384.0	All-purpose aluminium nozzle (DN 35) with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	☐
Wet/dry floor nozzle, advanced plastic, DN 40	17	2.889-117.0	The wet/dry floor nozzle (DN 40) permits a quick squeegee/brush change and is suitable for wet vacuum cleaning of large areas.	☐
Crevice nozzles				
Crevice nozzle, NT, DN 40, plastic, 300 mm	18	5.130-655.0	Plastic crevice nozzle in nominal width DN 40 for Kärcher wet and dry vacuum cleaners. Especially suitable for vacuuming out areas that are difficult to reach, such as joints, crevices and corners.	☒
Crevice nozzle, DN 35, plastic, length 210 mm	19	2.889-130.0	With the DN 35 plastic crevice nozzle, corners and crevices can be vacuumed quickly and thoroughly. Length: 210 mm.	☐
Crevice nozzle, NT, DN 35, metal, 500 mm long	20	6.900-922.0	The metal crevice nozzle (DN 35) enables vacuuming in crevices and corners. Length: 500 mm.	☐
Crevice nozzle, NT, DN 40, metal, 400 mm	21	6.905-817.0	Metal crevice tool (DN 40) for vacuuming in crevices and corners. Length: 400 mm.	☐
All-purpose brushes				
All-purpose brush	22	6.903-863.0	Natural bristles (ox hair), bristle element 120 × 45 mm.	☐
Car cleaning nozzles				
Car nozzle, ID 40, 90 mm	23	6.900-952.0	For retrofitting older Kärcher wet and dry vacuum cleaner models with bends in DN 40: Flat angled, convenient, plastic car cleaning nozzle with a working width of approx. 90 mm.	☐
	24	2.840-095.0	Flat angled, convenient, plastic, DN 40 car cleaning nozzle specially designed for new Kärcher wet and dry vacuum cleaners with a clip system at the suction hose. Working width: Approx. 90 mm.	☐
Rubber suction tools, nose 45°				
Rubber suction tool, nose 45°	25	6.902-104.0	45° rubber suction nozzle (DN 35), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	☐
NT rubber suction nozzle, bevelled at 45°, DN 40	26	6.902-105.0	45° rubber suction nozzle (DN 40), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	☐
Pipe dusting nozzles				
Pipe brush 35/100	27	6.903-035.0	Plastic, pipe diameter 100 mm	☐
Pipe brush 35/200	28	6.903-036.0	Plastic, pipe diameter 200 mm	☐

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR NT 75/2 AP ME TC

1.667-292.0



		Order no.	Description	
SUCTION TUBES				
Suction tubes, stainless steel				
Suction tube, 2 x, NT, DN 40, 550 mm long, stainless steel, suitable for: NT 50/1, NT 55/2, NT 65/2, NT 70/2, NT 70/3, NT 75/2	29	2.889-194.0	The suction tube set consists of 2 suction tubes made of high-quality stainless steel (DN 40 and 550 mm long each). For Kärcher wet and dry vacuum cleaners.	■
Suction tube, DN 35, 505 mm, stainless steel	30	6.902-154.0	Suction tube made of high-quality stainless steel in DN 35 and 505 mm long for wet and dry vacuum cleaners from Kärcher.	□
Suction tube, NT, DN 40, 550 mm long, stainless steel, suitable for: AP 100/50, NT 55/2, NT 65/2, NT 70/2, NT 70/3, NT 72/2, NT 75/2, NT 561, NT 611, NT 802 IV	31	6.902-081.0	Suction tube made of high-quality stainless steel in nominal width DN 40 and 550 mm long for wet and dry vacuum cleaners from Kärcher.	□
Suction tube, NT, DN 40, 1000 mm long, stainless steel, suitable for: NT 55/2, NT 65/2, NT 70/2, NT 70/3, NT 72/2, NT 75/2, NT 561, NT 611, NT 802 IV	32	6.906-531.0	The suction tube made of high-quality stainless steel (DN 40 and 1000 mm long) is suitable for wet and dry vacuum cleaners from Kärcher.	□
Suction tubes, metal				
Suction tube, NT, DN 35, 505 mm long, chrome-plated steel, suitable for: NT 25/1, NT 27/1, NT 30/1, NT 35/1, NT 40/1, NT 48/1, NT 50/1, NT 55/2, NT 65/2, NT 70/2, NT 70/3, NT 72/2, NT 75/1, NT 75/2, NT 611, NT 802 IV	33	6.900-514.0	The suction tube made of chrome-plated steel (DN 35, 505 mm long) is suitable for wet and dry vacuum cleaners from Kärcher.	□
SUCTION HOSES				
Suction hoses with clip system 2.0 (compatible with vacuum cleaners from model year 2017 on)				
Suction hose, NT, DN 40, length 4 m, clip 2.0, bayonet 2.0	34	2.889-138.0	The suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	■
Suction hose, NT, DN 35, length 4 m, electrically conductive, clip 2.0, bayonet 2.0	35	2.889-137.0	The electrically conductive suction hose in nominal width DN 35 and with 4 m length is suitable for use with wet and dry vacuum cleaners from Kärcher.	□
Suction hose, NT, DN 40, length 2.5 m, clip 2.0, bayonet 2.0	36	2.889-139.0	The suction hose in nominal width DN 40 and with 2.5 m length is suitable for use with wet and dry vacuum cleaners from Kärcher.	□
Suction hose, NT, DN 40, length 4 m, oil-resistant, clip 2.0, bayonet 2.0	37	2.889-140.0	The oil-resistant suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners from Kärcher.	□
Suction hose, NT, DN 40, length 4 m, electrically conductive, clip 2.0, bayonet 2.0	38	2.889-141.0	The electrically conductive suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	□
Suction hose, NT, DN 40, length 2.5 m, electrically conductive, clip 2.0, bayonet 2.0	39	2.889-142.0	The electrically conductive suction hose in nominal width DN 40 and with 2.5 m length is suitable for use with wet and dry vacuum cleaners.	□
Extension hose, NT, DN 40, length 2.5 m, clip 2.0, connecting adapter	40	2.889-146.0	The extension hose in nominal width DN 40 and with 2.5 m length is suitable for use with wet and dry vacuum cleaners from Kärcher.	□
Repair kit for suction hoses DN 40, Clip 2.0	41	2.889-150.0	Repair kit ID 40 for the new clip system.	□
Hose connection				
Adapter, ID 32/35, with internal thread	42	6.902-077.0	Electrically non-conductive adapter with internal thread. For connecting two suction hoses without connectors. Suitable for DN 32 or DN 35.	□

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR NT 75/2 AP ME TC

1.667-292.0



		Order no.	Description	
SUCTION HOSES				
Hose connection				
Connecting adapter, ID 40, with internal thread	43	6.900-286.0	Electrically non-conductive adapter with screw thread at both ends. For connecting 2 DN 40 suction hoses without connectors.	☐
Suction hoses with clip system 1.0 (compatible with vacuum cleaners up to model year 2016)				
Repair kit for suction hoses DN 40 Clip 1.0	44	2.639-873.0	Repair set (C40) includes threaded hose adapters (without bayonet adapter) for industrial NT vacuum cleaners with clip system.	☐
Extension hose, NT, DN 40, length 2.5 m, clip 1.0, connecting adapter	45	6.906-344.0	The extension hose in nominal width DN 40 and with 2.5 m length is suitable for use with wet and dry vacuum cleaners.	☐
Suction hose with bend, NT, DN 40, length 4 m, clip 1.0, bayonet 1.0	46	4.440-678.0	The suction hose with bend in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	☐
Suction hose, NT, DN 40, length 10 m, clip 1.0, bayonet 1.0	47	6.906-279.0	The suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners.	☐
Suction hose, NT, DN 40, length 4 m, clip 1.0, bayonet 1.0	48	6.906-321.0	The suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	☐
Suction hose, NT, DN 40, length 4 m, oil-resistant, clip 1.0, bayonet 1.0	49	6.906-714.0	The oil-resistant suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	☐
Suction hose with bend and PFC module, NT, DN 40, length 4 m, electrically conductive, clip 1.0, bayonet 1.0	50	4.440-728.0	The electrically conductive suction hose with bend and PFC module in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	☐
Suction hose, NT, DN 40, length 16 m, clip 1.0, bayonet 1.0	51	6.906-635.0	The suction hose in nominal width DN 40 and with 16 m length is suitable for use with wet and dry vacuum cleaners.	☐
Suction hose, NT, DN 40, length 10 m, electrically conductive, clip 1.0, bayonet 1.0	52	6.906-877.0	The electrically conductive suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners.	☐
Suction hoses with cone connection				
Suction hose, NT, DN 40, length 4 m, cone, bayonet 1.0	53	4.440-263.0	The suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	☐
Suction hose, NT, DN 40, length 4 m, oil-resistant, cone, bayonet 1.0	54	4.440-303.0	The oil-resistant suction hose in nominal width DN 40 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	☐
Suction hose, NT, DN 40, length 10 m, cone, bayonet 1.0	55	4.440-463.0	The suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners.	☐
Suction hose, NT, DN 40, length 10 m, electrically conductive, cone, bayonet 1.0	56	4.440-466.0	The electrically conductive suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners.	☐

☐ Available accessories.

ACCESSORIES FOR NT 75/2 AP ME TC

1.667-292.0



		Order no.	Description	
SUCTION HOSES				
Suction hoses with cone connection				
Suction hose, NT, DN 40, length 10 m, oil-resistant, cone, bayonet 1.0	57	4.440-612.0	The suction hose in nominal width DN 40 and with 10 m length is suitable for use with wet and dry vacuum cleaners.	☐
Suction hose, NT, DN 50, length 4 m, cone, bayonet 1.0	58	4.440-264.0	The suction hose in nominal width DN 50 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	☐
Suction hose, NT, DN 50, length 3 m, cone, bayonet 1.0	59	4.440-328.0	The suction hose in nominal width DN 50 and with 3 m length is suitable for use with wet and dry vacuum cleaners.	☐
Suction hose, NT, DN 50, length 10 m, cone, bayonet 1.0	60	4.440-467.0	The suction hose in nominal width DN 50 and with 10 m length is suitable for use with wet and dry vacuum cleaners.	☐
Suction hose, NT, DN 50, length 4 m, oil-resistant, cone, bayonet 1.0	61	4.440-613.0	The oil-resistant suction hose in nominal width DN 50 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	☐
Suction hose, NT, DN 50, length 4 m, electrically conductive, cone, bayonet 1.0	62	4.440-616.0	The electrically conductive suction hose in nominal width DN 50 and with 4 m length is suitable for use with wet and dry vacuum cleaners.	☐
FILTER BAGS				
Fleece filter bags				
Fleece filter bags, 5 Piece(s), NT 65, NT 70, NT 72, NT 75, NT 90	63	2.885-753.0	Tear-resistant fleece filter bags of dust class M, suitable for Kärcher wet and dry vacuum cleaners. Contents: 5-pack.	☐
Paper filter bags				
Paper filter bags, 5 Piece(s), NT 48, NT 65, NT 70, NT 72, NT 75, NT 80, WET VAC	64	6.904-285.0	Premium 3-layer paper filter bags of dust class M, suitable for Kärcher wet and dry vacuum cleaners. Contents: 5-pack.	☐
FILTER T/ NT				
Flat pleated filter HEPA, dust class H				
HEPA-14 flat pleated filter	65	6.904-364.0	For Kärcher wet and dry vacuum cleaners: HEPA-14 (H14) flat pleated filter. Suitable for vacuuming hazardous dusts, coarse dirt and liquids.	☐
Wet filter bag				
Wet filter bag	66	6.904-252.0	Approved for dust class L, general cleaning, wet and dry, tear-resistant.	☐
Plastic sacks for dust-free disposal				
Plastic bag for dust-free disposal, 10 Piece(s), NT 65, NT 70, NT 72, NT 75, NT 602, NT 700, NT 702	67	6.900-698.0	PE plastic sack.	☐
Fabric filter				
Candle filter Wood, NT 65/2, NT 75/2	68	2.414-003.0	Wood cartridge filter made from textile material with PTFE coating and a brown label. For safely vacuuming large quantities of wood and fibre dust with the NT 65/2 and 75/2 twin-motor Tact vacuums.	☐
Membrane filter, NT 65, NT 70, NT 72, NT 75, NT 551, NT 602, NT 700, NT 702, NT 802, NT 993	69	6.904-282.0	Polyester needle fleece membrane/fabric filter – BIA-C -, washable up to 40°C, metal fibres for earthing. Suitable for virtually all industrial two-motor NT vacuum cleaners.	☐
CONNECTING SLEEVES				
Y-adapter kit				
Y-adapter kit	70	2.637-217.0	Plastic distributor – suitable for NT vacuum cleaners.	☐

☐ Available accessories.

ACCESSORIES FOR NT 75/2 AP ME TC

1.667-292.0



		Order no.	Description	
CONNECTING SLEEVES				
Connection adapter C ID (clip to cone)				
Adapter clip DN 35 on cone DN 35	71	5.407-005.0	Adapter clip system DN 35 for connecting suction tubes and small nozzles to cone DN 35. Perfect for vehicle interior cleaning, even without the connection of other nozzles.	☐
Adapter clip DN 40 to cone DN 40	72	5.407-006.0	For connecting small nozzles and suction tubes with cone DN 40: Adapter clip system DN 40. Ideal for vehicle interior cleaning tasks, with no need to connect additional nozzles.	☐
Connection adapter C DN 35	73	5.407-112.0	C 35 hose connector for DN 35 accessory, electrically conductive.	☐
Electrically conductive DN 40 connection adapter for DN 35 accessories	74	5.407-109.0	Electrically conductive adapter (C 40) with DN 35 connection for connecting DN 35 accessories to an industrial C 40 or C-DN 40 suction hose. Suitable for NT vacuum cleaners.	☐
Connection adapter C DN 40	75	5.407-111.0	C 40 hose connector for DN 40 accessory, electrically conductive.	☐
Connection adapter for power tools, clip connection				
Power tool connection adapter, DN 26-36, electrically conductive	76	5.453-042.0	3-way plastic adapter. For DN 26 to DN 36. For connecting power tools to an industrial C or C-DN 35 suction hose. Suitable for NT vacuum cleaners.	☐
Connection adapter for power tools, C 35, electrically conductive	77	5.453-048.0	Inside Ø 25.4 mm, outside Ø 34.6 mm/ 38 mm, electrically conductive. Only NT vacuums.	☐
	78	5.453-050.0	Inside Ø 27 mm, outside Ø 36.5 mm/38.8 mm, electrically conductive. Only NT vacuums.	☐
Adapter for electric power tools, screwable				
Adapter for electric power tools, screwable, ID 35	79	5.453-016.0	3-way plastic adapter with fitting instructions. For DN 26 to DN 36. For connecting to an industrial DN 35 suction hose.	☐
	80	5.453-026.0	Inside Ø 28.6 mm, outside Ø 37.3/38.8 mm.	☐
	81	6.902-059.0	Electrically conductive power tool adapter, threaded. Internal diameter: 32 mm.External diameter: 39 mm.	☐
	82	6.902-095.0	2-way power tool adapter, threaded. For connecting to an industrial DN 35 suction hose. Internal diameter: 28 mm.External diameter: 34 mm and 38.8 mmSuitable for NT vacuum cleaners.	☐
Reducing sleeves				
NT reducer from DN 40 to DN 35, electrically conductive	83	5.407-108.0	Threaded reducer - from C-40 to DN 35. Suitable for NT vacuum cleaners.	☐
Reducer adapter from DN 40 to DN 35	84	6.902-017.0	Reducer, enabling accessories (upholstery nozzle, crevice nozzle, etc.) with a DN 35 connection adapter to be connected to accessory parts (bend or suction tube) that have a DN 40 connection adapter.	☐

☐ Available accessories.

ACCESSORIES FOR NT 75/2 AP ME TC

1.667-292.0



		Order no.	Description	
CONNECTING SLEEVES				
Reducing sleeves				
NT reduction bushing with clip system for DN 40 suction hoses on accessory DN 35	85	5.407-113.0	Reducer (C 40 to C 35) for connecting accessories with C-35 clip connection to suction hoses with C 40 clip system.	☐
Reducer from ID 35 to ID 32	86	6.902-072.0	Reducer with internal connecting cone DN 32. Ideal for accessories from the industrial vacuum cleaner range in combination with industrial NT vacuum cleaners.	☐
Reduction/expansion adapter kit				
Set of reducers / adapter sleeves	87	2.860-117.0	DN 40/35, DN 35/32 (tube -> nozzle), plastic.	☐
TARGET-GROUP-SPECIFIC ACCESSORY KITS FOR VACUUM CLEANERS				
Professional cleaning kit NT DN 40	88	2.637-353.0	Single parts: 4 m suction hose (4.440-263.0), metal bend (6.900-276.0), 2x 0.5 m metal suction tubes (6.900-275.0), crevice nozzle (6.903-033.0), floor nozzle with rollers (6.903-051.0).	☐
Car cleaning accessory kit	89	2.862-166.0	Vehicle interior cleaning accessory kit in nominal width DN 35 for Kärcher wet and dry vacuum cleaners. The kit comprises various nozzles and adapter pieces in nominal widths DN 35 and DN 40.	☐
NT accessory kit for vacuuming chips, DN 50	90	2.640-760.0	Target group-specific robust connection set in DN 61 for cleaning work in combination with oil-resistant suction hose and rubber nozzle.	☐
OTHER ACCESSORIES NT				
Cyclone preseparator CS 40 Me	91	2.863-026.0	The highly efficient CS 40 Me cyclone preseparator for all Kärcher wet and dry vacuum cleaners is a specially designed accessory for fine dust applications on construction sites or in industry.	☐
Adapter for NT hoses with bayonet connection 1.0	92	5.031-436.0	Electroconductive adapter for connecting NT hoses with bayonet 1.0 connection of nominal widths DN 35, 40, 50 to the new accessory system for wet and dry vacuum cleaners from Kärcher.	☐
MODIFICATION KIT, NON-CONDUCTIVE MEDIA				
Attachment kit, non-conductive media Tact² + Ap	93	2.642-602.0	For switching off when vacuuming non-conductive fluids such as oils and greases	☐
OTHER ACCESSORIES SCRUBBER DRIERS				
Miscellaneous				
Extension cable	94	6.647-022.0	Extension cable, 20 m, 3x1.5 mm². With splash-proof earthing pin plug, strain relief and anti-kink sleeve.	☐

☐ Available accessories.