Product datasheet

Specifications



voltage release XF - 100..130 V DC/ AC 50/60 Hz

47352

Main

Range	MasterPacT	
Range of product	MasterPact NT MasterPact NW MasterPact NW DC	
Device short name	XF	
Product or component type	Voltage release	
Device application	Control	
Voltage release type	Closing coil	
voltage release type	Instantaneous voltage release	
control type	Standard	
[Uc] control circuit voltage	100130 V AC 50/60 Hz 100130 V DC	
Circuit breaker mounting mode	Fixed	
Range compatibility	Masterpact MasterPact NT Masterpact MasterPact NW Masterpact MasterPact NW DC	

Complementary

Operating threshold	0.851.1 Un closing	
Response time	55 ms +/- 10 % for MasterPact NT	
	70 ms +/- 10 % for MasterPact NW 800 A	
	70 ms +/- 10 % for MasterPact NW 1000 A	
	70 ms +/- 10 % for MasterPact NW 1250 A	
	70 ms +/- 10 % for MasterPact NW 1600 A	
	70 ms +/- 10 % for MasterPact NW 2000 A	
	70 ms +/- 10 % for MasterPact NW 2500 A	
	70 ms +/- 10 % for MasterPact NW 3200 A	
	70 ms +/- 10 % for MasterPact NW 4000 A	
	80 ms +/- 10 % for MasterPact NW 5000 A	
	80 ms +/- 10 % for MasterPact NW 6300 A	
Supply holding power	4.5 VA	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	6.3 cm
Package 1 Length	8.1 cm
Package 1 Weight	1.162 kg

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Contractual warranty

Warranty

18 months





Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	17
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances		
Packaging made with recycled cardboard	Yes	
Packaging without single use plastic	Yes	
SCIP Number	Ad764790-535b-4a4e-825e-50fd804b5824	
China RoHS Regulation	China RoHS declaration	
PVC free	Yes	

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Product contains halogen above thresholds
Take-back	No

Contact: +971507924960

