Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product datasheet

Specifications



MX shunt release, ComPacT NSX, rated voltage 220/240 VAC 50/60 Hz, 208/277 VAC 60 Hz, screwless spring terminal connections

LV429387

Main

Range	ComPacT
Range of product	ComPact NSX100250 ComPacT NSX100250 new generation ComPact NSX400630 ComPact NSX400630 new generation ComPact NSX100250 DC ComPact NSX100250 DC new generation ComPact NSX100250 DC PV ComPact NSX100250 DC PV new generation ComPact NSX100250 DC PV new generation ComPact NSX400630 DC ComPact NSX400630 DC ComPact NSX400630 DC PV ComPact NSX400630 DC PV ComPact NSX400630 DC PV
Device short name	MX TO THE TOTAL TOTAL TO THE TH
Product or component type	Voltage re <mark>lea</mark> se
Device application	Control
Voltage release type	Opening coil Shunt trip release
[Uc] control circuit voltage	220240 V AC 50/60 Hz 208277 V AC 60 Hz
Range compatibility	ComPacT new generation (ComPacT NSX new generation) ComPacT new generation (ComPacT NSX DC new generation) ComPact (ComPact NSX) ComPact (ComPact NSX DC) EasyPact (EasyPact CVS) PowerPact (PowerPact Multistandard)

Complementary

Operating threshold	0.71.1 x Un opening
Response time	50 ms
Control signal type	Impulse Maintained
Impulse duration	>= 20 ms
Supply inrush power	10 VA
Auxiliary connection terminal	Spring 0.51.5 mm² (AWG 20AWG 16)
Wire stripping length	7 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	4.400 cm
Package 1 Width	4.700 cm
Package 1 Length	6.200 cm
Package 1 Weight	120 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	7.200 cm
Package 2 Width	10.500 cm
Package 2 Length	23.700 cm
Package 2 Weight	1.248 kg
Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	7.844 kg
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Contractual warranty	

Recommended replacement(s)

18 months

Contact: +971507924960 Email: sales@industrytechstore.com Website: www.industrytechstore.com

Warranty

