



H3CR-A8 100-240VAC/100-125VDC

Timer, plug-in, 8-pin, 1/16DIN (48 x 48 mm), on/flicker-on/flicker-off/interval/one-shot-delay, 0.05s-300h, DPDT, 5 A

Specifications

Type	Analog
Installation type	Socket
Functions	Multi-functional
Size	1/16 DIN (48 x 48 mm)
Terminal	Plug-in
Operating mode	Flicker ON Start (Power ON Start), Interval (Power ON Start), ON Delay (Power ON Start), One-shot Output (Power ON Start)
Output type	Relay
Contact description	DPDT
Time range	0.05 s - 300 h
Supply voltage AC	100-240 V
Supply voltage DC	100-125 V
Number of pin contact	8
Inputs	No-voltage

Accessories



P3G-08

Socket, back-connecting, 8-pin, screw terminals



Y92A-48B

Protective cover for DIN 48x48 mm device, hard plastic



Y92F-30

Flush panel mounting adapter for DIN 48x48 mm device



Y92F-73

Adapter for H3CR replacement of STP-YMH timer

Related products



P2CF

P2CF is the H3CA/R and H5CN/X/Z Timers and H7CC/N/X/Z Counters sockets range

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



H3CR-A/-F/-G/-H Solid- state Timer Datasheet

EN PDF 7.44 MB



H3CR-A8_A8S Instruction Sheet

EN PDF 3.31 MB



Timers Brochure

EN PDF 9.85 MB

Contact: +971507924960
Email: sales@industrytechstore.com



TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 15 November, 2024. Click here for [terms of use](#).

INDUSTRIAL AUTOMATION | [INDUSTRIAL.OMRON.EU](https://www.industrial.omron.eu)

OMRON