

CR-P230AC2



Products → Low Voltage Products and Systems → Control Products → Electronic Relays and Controls
→ Interface Relays and Optocouplers

General Information

Extended Product Type:	CR-P230AC2
Product ID:	1SVR405601R3000
EAN:	4013614498251
Catalog Description:	CR-P230AC2 Pluggable interface relay 2c/o, A1-A2=230VAC, 250V/8A
Long Description:	The CR-P230AC2 pluggable interface relay is from the CR-P (pcb) relay range. This relay operates with a 230 V AC rated control supply voltage and has a 2 c/o (SPDT) output with contacts rated at 250 V / 8 A. Standard sockets, logic sockets, pluggable function modules, holder and marker are available as accessories.

Additional Information

CCC Certificate:	CCC_2007010303228779
CSA Certificate:	CSA_1587291
Contact Material:	silver-nickel alloy (AgNi)
Country of Origin:	Poland (PL)
Customs Tariff Number:	85364900
Data Sheet, Technical Information:	2CDC117001D0203
Declaration of Conformity - CE:	No declaration needed
Degree of Protection:	IP67
E-number:	4005310
EAC Certificate:	EAC_RU_C-PL.ME77.B.01873
EAN:	4013614498251
EPLAN Catalog Tree:	Electrical engineering / Relays, contactors / General
EPLAN Function Definition:	Coil / Coil, 2 connection points / Coil, general A1_A2 Change-over contact / Change-over contact, 3 connection points / Change-over auxiliary contact 12_11_14 Change-over contact / Change-over contact, 3 connection points / Change-over auxiliary contact 22_21_24
ETIM 4:	EC001437 - Switching relay
ETIM 5:	EC001437 - Switching relay
ETIM 6:	EC001437 - Switching relay
Environmental Information:	1SAA981009-2401
Function:	Pluggable pcb interface relay CR-P
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SVC405600M9000
Integrated Free-Wheeling Diode:	No
Interface Relay Type:	Pluggable Circuit Board (PCB)
Invoice Description:	CR-P230AC2 Pluggable interface relay 2c/o, A1-A2=230VAC, 250V/8A
Manual Operation:	No
Maximum Switching Voltage:	250 V
Minimum Order Quantity:	10 piece
Number of Contacts CO:	2
Number of Contacts NC:	0
Number of Contacts NO:	0
Number of LEDs:	0
Object Classification Code:	K

Output:	2 c/o (SPDT) contacts
Output Current:	8 A
Output Signal:	250 V / 8 A
Package Level 1 EAN:	4013614373060
Package Level 1 Gross Weight:	0.157 kg
Package Level 1 Height:	28 mm
Package Level 1 Length:	17 mm
Package Level 1 Units:	10 piece
Package Level 1 Width:	332 mm
Power Loss:	Approximately 2 W
Product Main Type:	CR-P
Product Name:	Pluggable Interface Relay
Product Net Depth:	29 mm
Product Net Height:	15.7 mm
Product Net Weight:	0.014 kg
Product Net Width:	12.7 mm
RMRS Certificate:	RMRS_1740019250
Rated Control Supply Voltage (U _s):	230 V AC
Rated Operational Current (I _o):	8 A
Regulatory Compliance Mark (RCM):	No
RoHS Date:	1146
RoHS Information:	1SVD981001-4400
RoHS Status:	Following EU Directive 2011/65/EU
Selling Unit of Measure:	piece
Short Description:	CR-P230AC2 Pluggable interface relay
Standards:	IEC/EN 61810-1
Sub-Function:	Relay w/o built in LED
UNSPSC:	39121500
UR Certificate:	UR_E244330
VDE Certificate:	VDE_40019129
cUR Certificate:	cUR_E244330
eClass:	7.0 27371601

