



#### NT 55/1 Tact

The NT 55/1 Tact is a handy and strong wet/dry vacuum cleaner for commercial applications. It is equipped with the innovative and patented fully automated filter cleaning system TACT. Serially the NT 55/1 Tact provides a robust handle and an oil-resistant drain hose. The NT 55/1 Tact is equipped with full accessory that can easily be retained in the integrated accessory storage.

#### 1 Ergonomic push handle

■ The NT 55/1 Tact has an ergonomic push handle for easy transport.

#### 2 On-board accessory storage

 On-board storage for full range of accessories. Includes 2 hooks for suction hose and power cord.

## **TECHNICAL DATA AND EQUIPMENT**





#### NT 55/1 Tact

- Tact automatic filter cleaning system
- Push handle and drain hose
- On-board storage on the casing head

Technical data		
Order no.		1.146-820.0
EAN code		4039784722606
Current type	Ph / V / Hz	1 / 220 - 240 / 50 - 60
Air flow	I/s	74
Vacuum	mbar / kPa	254 / 25.4
Container capacity	I	55
Container material		Plastic
Rated input power	W	1380
Standard nominal width		DN 35
Sound pressure level	dB(A)	69
Number of motors		1
Weight	kg	16
Dimensions (L × W × H)	mm	580 × 380 × 870

Equipment				
Suction hose	m	2.5 / with bend	Push handle	
Suction tube	piece(s) × m	2 × 0.5 / Stainless steel	Protection class	II
Filter bag	piece(s)	1 / Fleece	Stop swivel castor	
Wet/dry floor nozzle	mm	300		
Crevice nozzle		•		
Drain hose (oil-resistant)				
Automatic cut-out features at max. filling quality		•		
Eco filter system				
Flat pleated filter		Paper		
Filter cleaning		Tact Filter Clean		
Sturdy bumper		•		

■ Included in the scope of supply.

























		Order no.	Quantity	ID	Length	Width	Price	Description
Flat pleated filter, paper			<u>'</u>	<u>'</u>				
Dry flat pleated filter	1	6.904-367.0	1 piece(s)					Dry flat pleated filter made from cellulose fibre material with a green label. Suitable for vacuuming fine dust and coarse dirt from dust classes L and M.
Bend, plastic								
Plastic bend	2	5.031-718.0	1 piece(s)	35				Plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models (except NT Eco M and NT Eco H).
Bend, plastic, electrically conductive	3	5.031-939.0	1 piece(s)	35				Electrically conductive plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611   Eco models.
	4	5.032-427.0	1 piece(s)	40				Electrically conductive plastic bend (DN 40) with C-40 clip system, suitable for all NT vacuum cleaners.
Plastic bend	5	5.031-904.0	1 piece(s)	40				Plastic bend (DN 40) with C-40 clip system, suitable for all NT models.
PFC module, C-35, electrically conductive	6	4.060-478.0	1 piece(s)	35				For activating semi-automatic filter cleaning, electrically conductive.
Suction tubes, stainless steel	ı	ı	1		,			
Suction tube	7	6.902-154.0	1 piece(s)	35	0.5 m			0.5 m long stainless steel suction tube (ID 35) for wet and dry vacuum cleaners. Ideal for frequent wet vacuuming applications and for vacuuming corrosive components.
	8	6.902-081.0	1 piece(s)	40	0.5 m			Stainless steel suction tube (DN 40, 0.5 m) only suitable for NT vacuum cleaners. $\hfill\Box$
	9	6.906-531.0	1 piece(s)	40	1 m			Stainless steel suction tube (DN 40, 1.0 m) only suitable for NT vacuum cleaners.
Nozzle kits	ı	1	1	1				
Nozzle kit	10	2.860-116.0	1 piece(s)	DN 35				Nozzle kit for all NT vacuum cleaners with DN 35 accessories includes crevice tool, upholstery tool, round brush (x3)
Flat pleated filter HEPA, dust class	1	1 5 00 4 242 0	4 -:(-)	1	I	ı	ı	UEDA surface filters short aloca II (UEDA 42), with aloca fi
HEPA flat pleated filter	11	6.904-242.0	1 piece(s)					HEPA surface filter - dust class H (HEPA 13) - with glass-fibre layers increases filter capacity when vacuuming health-endangering and carcinogenic dust.
Flat pleated filter, PES								
Flat pleated filter, PES	12	6.904-360.0	1 piece(s)					Flat pleated filter (PES) – BIA-C dust class M: rotproof polyester fleece, ideal for wet use and abrasives. Standard for NT 35/1 Eco BS and NT 55/1 Eco BS.
Flat pleated filter, PTFE	ı	ı	1	1				
Ultimate flat pleated filter	13	6.907-455.0	1 piece(s)					Ultimate flat pleated filter made from PES/PTFE fibre material with a black label. For the toughest applications when vacuuming liquids, fine dust and coarse dirt from dust classes M and L.
Coarse dirt filter for wet vacuumin	g							
Coarse dirt filter	14	6.904-287.0	1 piece(s)					Coarse dirt filter with perforated metal plate and foam seal suitable for wet pick up - NT 611 Eco K & KF models.
Wet filter bag				,				
Wet filter bag	15	6.904-211.0	5 piece(s)					Tear-resistant special/wet filter bag for dust class L, suitable for dry and wet pick up. Suitable for NT 561, NT 611 and NT ☐ 611 K.
Plastic sacks for dust-free disposal	1			,				
Plastic sacks for dust-free disposal	16	6.596-886.0	10 piece(s)					PE plastic sack.

























	_	1	1					
					ļ			
		Order no.	Quantity	ID	Length	Width	Price	Description
Fabric filter					1	ı		
Membrane filter	17	6.904-212.0	1 piece(s)					Polyester needle fleece membrane/fabric filter, washable up to 40°C, suitable for all NT 361 Eco to NT 611 Eco versions
Fleece filter bags								as an alternative to a filter bag.
Fleece filter bags	18	6.907-480.0	5 piece(s)		1			Fleece filter bag, tear-resistant, dust class M.
Adv fleece filter bags	19	6.907-361.0	5 piece(s)					Fleece filter bag, extra tear-resistant, dust class M.
Bends, stainless steel	1 1 3	0.307 301.0	3 piece(3)					Treece filter bag, extra tear resistant, dost class wi.
Bend, stainless steel, ID 35	20	6.903-141.0	1 piece(s)	35	1	l		Stainless steel and crooked, ID 35
Bend, stainless steel, ID 40	21	6.902-079.0	1 piece(s)	40				Stainless steel and crooked, ID 40
Bends, metal	21	0.302 073.0	1 piece(s)	140				Statiliess steel and crooked, 15 40
Bend, metal	22	6.900-519.0	1 piece(s)	35				Robust, chromium-plated metal bend (DN 35), can be used instead of a plastic bend (with clip system adapter 5.407-112.0, C 35-DN 35, plastic, el.).
	23	6.900-276.0	1 piece(s)	40				Robust, chromium-plated metal bend (DN 40), can be used instead of a plastic bend (with clip system adapter 5.407-111.0, C 40-DN 40, plastic, el.).
Floor nozzles								
Wet and dry floor nozzle	24	6.906-512.0	1 piece(s)	35		300 mm		All-purpose plastic nozzle (DN 35) with 300 mm working width. With side rollers, brush strips (6.903-278.0) and squeegees (6.903-277.0). Only for NT vacuum cleaners.
Multi-purpose nozzle, wet/dry	25	6.903-018.0	1 piece(s)	40		370 mm		All-purpose aluminium nozzle with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.
	26	6.906-383.0	1 piece(s)	40		450 mm		All-purpose aluminium nozzle (DN 40) with 450 mm working width. With height-adjustable side rollers, brush strips (6,903-065.0) and oil-resistant squeegees (6,906-146.0). Only for NT vacuum cleaners.
	27	6.906-384.0	1 piece(s)	35		370 mm		All-purpose aluminium nozzle (DN 35) with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.
Wet/Dry floor nozzle standard	28	2.889-173.0	1 piece(s)	35		300 mm		300 millimetre width, anthracite coloured wet/dry floor nozzle, NW 35. With easy-to-change inserts. Incl. brush strips and squeegees.
Wet/Dry floor nozzle standard DN40	29	2.889-174.0						Standard floor nozzle, anthracite, in nominal diameter 40, with brush strips and squeegees. Suitable for all wet and dry applications.
DN 40 wet/dry floor nozzle	30	6.907-408.0	1 piece(s)	40		360 mm		Multi-purpose nozzle (ID 40), plastic, 360 mm working width. With side rollers, brush strips (6.905-878.0) and squeegees (6.905-877.0).
Wide nozzles								· · · · · · · · · · · · · · · · · · ·
Wide nozzle	31	4.130-401.0	1 piece(s)	40		611 mm		Metal, height-adjustable, brush strips, rubber blades (only for NT 55/1 Eco/Tact & NT 611 Eco/Tact versions)
Rubber suction tools, nose 45°								
Rubber suction tool, nose 45°	32	6.902-104.0	1 piece(s)	35	220 mm			45° rubber suction nozzle (DN 35), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.
	33	6.902-105.0	1 piece(s)	40	220 mm			45° rubber suction nozzle (DN 40), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.

<sup>■</sup> Included in the scope of supply. 

Available accessories.























		Order no.	Quantity	ID	Length	Width	Price	Description
Combi-nozzles, dry								
Combi-nozzle, dry	34	6.906-511.0	1 piece(s)	35		270 mm		Combination floor tool with changeover function, plastic (272 mm). With stainless steel base plate, thread catcher 6.905-417.0 and DN 35 connection.
Suction brushes								
Suction brush	35	6.903-862.0	1 piece(s)	35		70 mm		Rotatable suction brush (DN 35) with natural bristles (cow hair). Bristle size 70x45 mm. Only CV and NT vacuum cleaners.
Turbo nozzles								
Turbo upholstery nozzle	36	2.860-113.0	1 piece(s)	32		160 mm		Plastic turbo upholstery nozzle (DN 35/32, 160 mm) with reduction sleeve.
Turbo floor nozzle	37	2.860-114.0	1 piece(s)	32		270 mm		Plastic turbo floor nozzle (DN 35/32, 270 mm) with reduction sleeve.
Suction tubes, plastic								
Suction tube	38	6.900-384.0	1 piece(s)	35	0.5 m			Plastic suction tube (DN 35, 1x0.5 m) only suitable for BV and T vacuum cleaners.
Suction tubes, metal								
Suction tube	39	6.900-275.0	1 piece(s)	40	0.55 m			The suction tube (NW 40, 1 x 0.55 m) made from chrome-plated metal is standard in almost all commercial vacuum cleaners with twin motor. Optional for commercial single motor NT vacuum cleaner with suction hose NW 40.
Suction tube set, chrome-plated, NW 35 550 mm	40	2.889-191.0	1 piece(s)	35	550 mm			Suction tube set, metal-chrome-plated, NW 35, 2-part, each 0.55 millimetres.
Paper filter bags								
Paper filter bags	41	6.904-208.0	5 piece(s)					5 paper filter bags (BIA-(U, S, G, C) dust class M) with reinforced outer ply. Standard for NT 561/611 Eco/te/M/TEA/M A, optional for NT 361 Eco BS/611 Eco BS.
Other								
Drilling dust nozzle	42	2.679-000.0	1 piece(s)					Drilling dust nozzle for dust-free vacuuming of boreholes. Suitable for dry and wet and dry vacuum cleaners from Kärcher.
CS 40 Me	43	2.863-026.0	1 piece(s)					The highly efficient CS 40 Me cyclone preseparator for all Kärcher wet and dry vacuum cleaners is a specially designed accessory for fine dust applications on construction sites or in industry.

<sup>■</sup> Included in the scope of supply. 

Available accessories.































		Order no.	Anzahl	Nennweite	Länge	Price	Description
Complete suction hoses (clip syster	n)						
Suction hose	1	4.440-626.0	1 piece(s)	35	2.5 m		With bend, C ID 35.
Suction hose, electrically conductive	2	4.440-653.0	1 piece(s)	35	2.5 m		With bend, electrically conductive, C ID 35.
Suction hose	3	2.889-161.0	1 piece(s)	35	2 m		2 m long suction hose with new clip fastening, DN 35. Ideal for Kärcher dry vacuum cleaners. Robust, flexible and durable.
Repair kits							
Repair kit, C 35	4	2.639-682.0	1 piece(s)	35			Suction hose repair kit (clip system).
Suction hoses (clip system)							
Suction hose	5	6.906-241.0	1 piece(s)	35	4 m		With bayonet and clip connection.
	6	6.906-275.0	1 piece(s)	35	2.5 m		With bayonet and clip connection, electrically conductive,
	7	6.906-500.0	1 piece(s)	35	4 m		C-35.
	8	6.906-321.0	1 piece(s)	40	4 m		With bayonet and clip connection, C 40.
	9	6.906-714.0	1 piece(s)	40	4 m		With bayonet and clip connection, oil-resistant, C-45.
	10	6.906-546.0	1 piece(s)	40	4 m		With bayonet and clip connection, electrically conductive, C 40.
	11	6.906-877.0	1 piece(s)	40	10 m		With bayonet and clip connection, electrically conductive, C-40.
Suction hose (clip system), C 35, 10 m	12	6.906-242.0	1 piece(s)	35	10 m		With bayonet and clip connection.
Suction hoses complete							
Suction hose, complete	13	4.440-461.0	1 piece(s)	27	7 m		Plastic, with connection bushing for power tools.
Connecting sleeves							
Adapter, ID 32/35, with internal thread	14	6.902-077.0	1 piece(s)	32			For connecting two suction hoses (not ESB 28 and 34).
Connecting adapter, ID 40, with internal thread	15	6.900-286.0	1 piece(s)	40			For connecting two suction hoses, threaded at both ends.
Connecting sleeve, ID 61, with female thread	16	6.902-078.0	1 piece(s)	61			
Extension hoses (clip system)							
Extension hose	17	6.906-237.0	1 piece(s)	32	2.5 m		For all C-32 and C-35 hoses.
	18	6.906-344.0	1 piece(s)	40	2.5 m		For all C-40 hoses.

 $<sup>\</sup>blacksquare$  Included in the scope of supply.  $\qed$  Available accessories.





























		T	1					_
		Order no.	Anzahl	Nennweite		Price	Description	
Connection adapter for power tools	, clip-	on, electrically c	onductive		<u> </u>			
Connection adapter for power	1	5.453-042.0	1 piece(s)	35			Plastic, adjustable from ID 26-36 (Te / Eco M / H), electrical	-
tools, C 35, electrically conductive							ly conductive.	₽
	2	5.453-048.0	1 piece(s)	35			Inside Ø 25.4 mm, outside Ø 34.6 mm / 38 mm, electrically conductive.	
Connection Adaptor for power	3	5.453-049.0	1 piece(s)	35			Inside Ø 28.6 mm, outside Ø 37.3 mm / 38.8 mm, electrically	У П
tools, C 35, electrically conductive			, , , , ,				conductive. Only wet and dry suction adapter.	
Connection adapter for power	4	5.453-050.0	1 piece(s)	35			Inside Ø 27 mm, outside Ø 36.5 mm / 38.8 mm, electrically	П
tools, C 35, electrically conductive							conductive.	二
Connection Adaptor for power	5		1 piece(s)	35			Inside Ø 32 mm, outside Ø 39 mm, electrically conductive.	
tools, C 35, electrically conductive	6	5.453-052.0	1 piece(s)	35			Inside Ø 28 mm, outside Ø 34 mm / 38.8 mm, electrically	
Compatible advances District	-> -1-		N				conductive.	二
Connection adapter C ID (clip to cor		1	1	1		1		
Connection adapter C DN 35	7	5.407-112.0	1 piece(s)	35			C 35 hose connection for ID 35 accessories, electrically conductive.	
Connection adapter C DN 40	8	5.407-109.0	1 piece(s)	40			C 40 hose connection for ID 35 accessories, electrically conductive.	
	9	5.407-111.0	1 piece(s)	40			C 40 hose connection for ID 40 accessories, electrically	+
		3.107 111.0	1 p.eee(s)				conductive.	
Adapter for electric power tools, so	rewab	ole						
Adapter for electric power tools,	10	5.453-016.0	1 piece(s)	35			Plastic, adjustable from ID 26-36.	
screwable, ID 35	11	5.453-026.0	1 piece(s)	35			Inside Ø 28.6 mm, outside Ø 37.3 mm / 38.8 mm.	
	12	6.902-059.0	1 piece(s)	35			Inside Ø 32 mm, outside Ø 39 mm.	
	13	6.902-095.0	1 piece(s)	35			Inside Ø 28 mm, outside Ø 34 / 38.8 mm, electrically con-	
							ductive.	╚
Expansion pieces (tube -> nozzle)								
Adapter ID 35 - 40 (tube -> noz-	14	6.902-084.0	1 piece(s)	35			From ID 35 to ID 40, plastic.	
zle)								Ľ
Reducing sleeves						1		
Reducer	15	5.407-108.0	1 piece(s)	40			From C 40 hose with outer thread 35 for connection bushing, screwable, ID 35.	
Reduction bushing	16	5.407-113.0	1 piece(s)	40			Reduction bushing from clip C 40 to clip C 35.	
Reducers (tube -> nozzle)					·			
Reducer	17	6.902-017.0	1 piece(s)	40			From ID 40 to ID 35, plastic.	
Reducer from ID 35 to ID 32	18	6.902-072.0	1 piece(s)	35			From ID 35 to ID 32, metal.	
Reduction/expansion adapter kit								
Set of reducers / adapter sleeves	19	2.860-117.0	1 piece(s)				ID 40/35, ID 35/32 (tube -> nozzle), plastic.	
■ Included in the scene of supp		□ Available ac						لنــــــــــــــــــــــــــــــــــــ

 $<sup>\</sup>blacksquare$  Included in the scope of supply.  $\qed$  Available accessories.

















		Order no.	ID		Price	Description	
Target-group-specific accessory kit	s for v	acuum cleaners					
Universal trade and industrial set	1	2.637-595.0	DN 35			Universal kit for industrial and commercial use.	
Heating boiler cleaning kit	2	2.638-852.0	DN 35			Heating boiler cleaning kit.	
Construction kit	3	2.637-352.0	DN 40			Construction kit.	
Professional cleaning kit	4	2.637-353.0	DN 40			Professional cleaning kit.	
Horse kit, electrically conductive	5	2.637-248.0	DN 40			Horse kit, electrically conductive.	
Wet and dry vacuuming kit, ID 40,	6	2.638-147.0	DN 40			Wet and dry vacuuming kit, electrically conductive.	
electrically conductive							$\perp \perp$
Oven kit	7	2.640-341.0	DN 35			Oven kit.	

<sup>■</sup> Included in the scope of supply. 

Available accessories.





		Order no.	Length	Colour	Quanti- ty	Price	Description
Miscellaneous							
Extension cable	1	6.647-022.0	20 m		1 piece(s)		Extension cable, 20 m, 3x1.5 mm <sup>2</sup> . With splash-proof earthing pin plug, strain relief and anti-kink sleeve.

 $<sup>\</sup>blacksquare$  Included in the scope of supply.  $\hfill\Box$  Available accessories.

Contact: +971507924960

Email: sales@industrytechstore.com Website: www.lndustrytechstore.com

