Product datasheet

Specifications



Acti9 iC60N 3P 63A C Miniature Circuit breaker

A9F44363

Main

Range	Acti9	
product name	Disbo iC60	
Product or component type	Miniature circuit-breaker	
Device short name	IC60N	
Poles description	3P	
Number of protected poles	3	
[In] rated current	63 A	
network type	AC	
Trip unit technology	Thermal-magnetic	
Curve code	С	
Breaking capacity	6000 A Icn at 415 V AC 50/60 Hz conforming to EN/IEC 60898-1 36 kA Icu at 12133 V AC 50/60 Hz conforming to EN/IEC 60947-2 20 kA Icu at 220240 V AC 50/60 Hz conforming to EN/IEC 60947-2 10 kA Icu at 380415 V AC 50/60 Hz conforming to EN/IEC 60947-2 6 kA Icu at 440 V AC 50/60 Hz conforming to EN/IEC 60947-2 10 kA Icu at <= 180 V DC conforming to EN/IEC 60947-2	
Utilisation category	Category A conforming to EN/IEC 60947-2	

Complementary

Network frequency	50/60 Hz	
[Ue] rated operational voltage	400 V AC 50/60 Hz	
Magnetic tripping limit	8 x In +/- 20 %	
[Ics] rated service breaking capacity	27 kA 75 % conforming to EN/IEC 60947-2 - 12133 V AC 50/60 Hz 15 kA 75 % conforming to EN/IEC 60947-2 - 220240 V AC 50/60 Hz 7.5 kA 75 % conforming to EN/IEC 60947-2 - 380415 V AC 50/60 Hz 4.5 kA 75 % conforming to EN/IEC 60947-2 - 440 V AC 50/60 Hz 6000 A 100 % conforming to EN/IEC 60898-1 - 415 V AC 50/60 Hz 15 kA 100 % conforming to EN/IEC 60947-2 - 100133 V DC	
Limitation class	3 conforming to EN/IEC 60947-2	
[Ui] rated insulation voltage	500 V AC 50/60 Hz	
[Uimp] rated impulse withstand voltage	6 kV conforming to EN/IEC 60947-2	
Contact position indicator	Yes	
Control type	Toggle	
Local signalling	Trip indicator	
Mounting mode	Clip-on	
Mounting support	Rail	

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

10 Feb 2025 Life Is On Schneider

9 mm pitches	6
Height	85 mm
Width	54 mm
Depth	78.5 mm
Product weight	0.375 kg
Colour	White
Mechanical durability	20000 cycles
Electrical durability	10000 cycles
Provision for padlocking	Padlockable
Connections - terminals	Single terminal (top or bottom) 135 mm² rigid Single terminal (top or bottom) 125 mm² flexible
Wire stripping length	14 mm for top or bottom connection
Tightening torque	3.5 N.m top or bottom
Earth-leakage protection	Separate block

Environment

Standards	EN/IEC 60947-2 EN/IEC 60898-1	
IP degree of protection	IP20 conforming to IEC 60529	
Pollution degree	3 conforming to EN/IEC 60947-2	
overvoltage category	IV	
Tropicalisation	2 conforming to IEC 60068-1	
Relative humidity	95 % at 55 °C	
Ambient air temperature for operation	-3570 °C	
Ambient air temperature for storage	-4085 °C	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.5 cm
Package 1 Width	5.4 cm
Package 1 Length	9.5 cm
Package 1 Weight	381 g
Unit Type of Package 2	BB1
Number of Units in Package 2	4
Package 2 Height	8.5 cm
Package 2 Width	9.8 cm
Package 2 Length	22 cm
Package 2 Weight	1.575 kg
Unit Type of Package 3	S03
Number of Units in Package 3	44
Package 3 Height	30 cm

Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	17.832 kg





Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	94
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
SCIP Number	26ff71d1-98cf-4280-872 <mark>5-455b</mark> 9a6b2fb9
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	No

Contact: +971507924960 Email: sales@industrytechstore.com Website: www.industrytechstore.com

