

RECHARGEABLE

INTRANT™ DUAL-LIGHT ANGLE LIGHT

**NIGHTSTICK®**  
Life Depends on Light™




**Head rotates 90°** – directing beam exactly where it's needed most



**45° downward floodlight** lights an 8 foot walking area



**Easy-to-use with gloves**, the large switches **independently control** separate LEDs



**Heavy-duty, clip and V-ring** securely holds **tight to gear** in any situation

GRAB-N-GO  
CHARGING BASE



ALSO AVAILABLE IN SAFETY RED.



**205 LUMENS**

1-800-233-2155 • 1-469-326-9400 • [nightstick.com](http://nightstick.com)

# DUAL-LIGHT ANGLE LIGHT

## RECHARGEABLE

### ITEM NUMBER/UPC

XPR-5568RX (Red), 0 17398 80631 2  
XPR-5568RLB (Red, Light & Battery Only), 0 17398 80697 8  
XPR-5568GX (Green), 0 17398 80630 5

### CERTIFICATIONS

- CE, cULus, ATEX, IECEx, InMetro, UKCA, KOSHA  
- Meets requirements of NFPA

### PATENTS

- 9,713,217 10,119,663

### CASE MATERIAL

- Engineered polymer

### LUMENS/RUNTIME

#### FLASHLIGHT

- HIGH: 200L, 7 hrs. runtime  
- MEDIUM: 110L, 15 hrs. runtime  
- LOW: 60L, 27 hrs. runtime  
- STROBE

#### FLOODLIGHT

- HIGH: 100L, 7 hrs. runtime  
- MEDIUM: 40L, 15 hrs. runtime  
- SURVIVAL: 20L, 27 hrs. runtime

#### DUAL-LIGHT

- 205L, 7 hrs. runtime

### CANDELA

#### FLASHLIGHT

- HIGH: 40,256  
- MEDIUM: 15,625  
- LOW: 8,750

### BEAM DISTANCE

#### FLASHLIGHT

- HIGH: 401m  
- MEDIUM: 250m  
- LOW: 187m

### WATER RATING

- IP-67 (dustproof and waterproof)

### DROP RATING

- 2 meters

### DIMENSIONS

- LENGTH: 6.6 in (168mm)  
- WIDTH: 2.6 in (66mm)  
- DEPTH: 2.6 in (66mm)  
- HEAD DIAMETER: 2.1 in (53mm)  
- WEIGHT: 10.6 oz (301g)(with batteries)

### BATTERY

- Rechargeable Li-ion battery pack  
- AA Battery carrier (batteries not included)

### WARRANTY

- Limited lifetime warranty

### WHAT'S INCLUDED

- Angle light  
- Rechargeable Li-ion battery pack  
- AA battery carrier  
- Snap-in rapid charger (Charge Input: 24VDC max) Meets requirements of NFPA  
- AC & DC power supplies  
- Instruction manual

FL 1 STANDARD	SPOT HIGH	SPOT LOW	DUAL-LIGHT
	200 LUMENS	60 LUMENS	205 LUMENS
	7h	27h	7h
	401m		
	40256cd		

**Bayco Product, Inc. XPR-5568**  
640 S. Sanden Blvd., Wylie, TX 75098

Ex in FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS LISTED Ex in PRELIMINARY LOCAL PERIODS

For use with Bayco Li-ion Battery Pack 5568-BATT or 5568-CARRIER with 3 AA Energizer Type EN91 or E91 batteries only

Ex in op in I Ma Ex in op in I Ma Ex in op in I Ma

CLASS II & III DIV1 GRPS E-G T130°C CLASS I ZONE 0 AEx ia IIC T4 Ga

US Patents 9,713,217 & 10,119,663

CE 2575 UK CA 0359

Meets the requirements of NFPA-1971-8.6 (2013)

DEMCO 11 ATEX 1527 UL2000C20R IECEx UL 17.0082 20°C 5 Tamb C +40°C 3.7VDC Recharge 3.7VDC Li-ion 1P-67 Um: 10V

Control Drawing: 5568-CERT-DWG1-03 For Battery Charger Connection see Instruction Manual Drawing: 5562-68-MECH-DWG1-09

SEE INSTRUCTION MANUAL VOIR MANUEL

MFG MM-YY

CERTIFIED