

## Smart Diffusion Flammable Gas Detector

# GTD-2000Ex



### Features

- This detector is specialized for detecting combustible gases.
- It is designed with an explosion-proof structure, ensuring there is no risk of secondary explosions.
- Equipped with a display for easy monitoring and calibration.
- KFI-approved model integrated with the GTC-210A control panel.
- HART communication is supported.
- Remote calibration and program settings can be configured using a magnetic bar.
- The calibration process is simple enough to be completed by a single operator.
- Compatible with explosion proof warning lights (GTL-100) attached to the detector.

### Accessories




Cable gland



GTL-100



Rain cover



HART Module



Splash guard



Collecting cone

## Sensor Specification

\* = Refer to Toxic gas measuring range

Measuring method	Catalytic cell	Hot wire semiconductor cell	Thermal conductivity cell
Measuring gas	Flammable gas	Flammable gas	Flammable gas
Measuring range	0 ~ 100% LEL	0 ~ 2000ppm	0 ~ 100% Vol
Response time	< 15sec / 90% scale	< 15sec / 90% scale	< 15sec / 90% scale
Material	SUS316	SUS316	SUS316

## Detector Specification

Measuring type	Diffusion type
Accuracy	±3% / Full scale
Parameter control	Non intrusive control with a Magnet bar (Calibration, Maintenance)
Operation mode display	1-LED (Power)
Measuring value display	LCD display (Built in back light 2-Line, 8 Characters) / OLED type (Option)
Output signal	Analog : 4-20mA Analog output / Maintenance signal : 4mA / Calibration signal : 3mA / Fault signal : 0mA
Material	Aluminium alloy or Stainless steel
Cable entry thread	Standard : PF 3/4"   Option : PF 1/2" , M20 x 1.5P , M25 x 1.5P , NPT 1/2" , NPT 3/4"
Mounting type	2" Pole mount, Wall mount
Operating temperature	-40°C ~ 80°C
Operating humidity	5 ~ 99% RH (Non-condensing)
Dimensions	136(W) x 166(H) x 110(D) mm
Weight	1.4Kg (Aluminium alloy)   3.1Kg (Stainless steel)

## Detector Certification

Explosion-Proof Certification	KCs	Korea Explosion Proof Certification	Ex tD A21 IP66 T85°C, Ex d IIC T6, T5, T4		
	ATEX	European Explosion Proof Certification	Ex db IIC Gb T6, T5, T4		
	IECEX	International Explosion Proof Certification	Ex db IIC Gb T6, T5, T4		
	NEPSI	China Explosion Proof Certification	Ex db IIC T5 Gb		
	UL	U.S. Explosion Proof Certification	Class I, Division 1, Groups A,B,C,D		
	PESO	India Explosion Proof Certification	Ex db IIC T6/T5/T4 Gb		
	TIIS	Japan Explosion Proof Certification	Ex db IIC Gb		
	TRCU ex	Russian Explosion Proof Certification	1Ex d IIC T6...T4 Gb X		
	TS	Taiwan Explosion Proof Certification	Ex db IIC Gb T6/T5/T4		
Classification Society Certification	ECAS Ex	UAE Explosion Proof Certification	Ex db IIC Gb T6/T5/T4		
	KR	Korea Classification Society Certification	Other Certifications	HART	Communication Protocol Certification
	MED	European Classification Society Certification		SIL2	Safety Integrity Certification
	ABS	U.S. Classification Society Certification		CE(EMC)	European Electromagnetic Certification
	BV	France Classification Society Certification		CPA	China Measuring Instrument Certification
	DNV	Norwegian Classification Society Certification		-	Thailand Ministry of Energy Certification
	CCS	China Classification Society Certification		KC	Korea Electromagnetic Certification
	RS	Russian Classification Society Certification		KFI	Korea Fire Safety Certification
	LR	UK Classification Society Certification		PAC	Russia Measuring Instrument Certification
	RINA	Italian Classification Society Certification		CE(RoHS)	European Hazardous Substances Certification