

ABB Protection & Control Products

1SVR405650R0000

CR-PLS Logical socket Screw (CR-PLS)



Information

The CR-PLS socket is from the CR-P (pcb) relay range. The logical socket with safety isolation is suitable for CR-P relays with 1 or 2 c/o (SPDT) output contacts. The socket has screw connection terminals. Pluggable function modules, holder and marker are available as accessories.

Technical Specifications

EAN	4013614528569
Minimum Order Quantity	10 piece
Customs Tariff Number	85366990
Product Net Width	15.5 mm
Product Net Height	61 mm
Product Net Depth / Length	75 mm
Product Net Weight	0.045 kg
Function	Accessory for interface relays CR-P
Sub-Function	Socket for PCB relays
Sub-Function 2	Logical socket for pcb relay 1 c/o or 2 c/owith protective

Sub-Function 2	separation
Rated Operational Voltage	250 V
Output	none
Terminal Type	Screw Terminals
Rated Operational Current AC-12 (Ie)	(230 V) 2 A
Rated Insulation Voltage (Ui)	5 V
Mounting Position	1
Standards	CAN/CSA C22.2 No.14IEC/EN 63000IEC/EN 61984UL 508
Connecting Capacity Main Circuit UL/CSA	Flexible with Ferrule 2x 20-16 AWGRigid 2x 20-14 AWGStranded 2 x 20-14 AWG
Flammability According to UL94	V-0
Ambient Air Temperature	Operation -40 ... +70 °CStorage -40 ... +70 °C
Maximum Operating Altitude Permissible	2000 m
RoHS Status	Following EU Directive 2011/65/EU
Package Level 1 Units	box 10 piece
Package Level 1 Width	159 mm
Package Level 1 Depth / Length	80 mm
Package Level 1 Height	64 mm
Package Level 1 Gross Weight	0.452 kg
Package Level 1 EAN	4013614373077
Object Classification Code	K
ETIM 7	EC001456 - Relay socket
ETIM 8	EC001456 - Relay socket
ETIM 9	EC001456 - Relay socket
eClass	V11.0: 27371603
UNSPSC	39122335
E-Number (Finland)	2712755
E-Number (Sweden)	4005315

Contact: +971507924960
Email: sales@industrytechstore.com

