

Installation Guide

Pressure Transmitters

AKS 32, AKS 32R, AKS 33, AKS 2050, AKS 3000, AKS 3050, DST P310

060R9347		Kølemidler Refrigerants Kältemittel Réfrigérants Arbejdstemperatur Operating temperature Betriebstemperatur Température de fonctionnement	NH ₃ , R22, R134a, R404A, R407C, R410A, R507 et. Al. -40 – 85 °C / -40 – 125 °C	060R9347
----------	--	--	---	----------

Electrisk tilslutning, Electrical connection, Elektrische Verbindung, Raccordement électrique

	175201-802 SI-Units (bar) 	4 – 20 mA AKS 33, AKS 3000, AKS 3050, (DST P310) 	1-5 V, 1-6 V, 0-10 V AKS 32, AKS 3000, AKS 3050, (DST P310) 	10 – 90% AKS 32R, AKS 2050, (DST P310) 	Forbundet til kapsling Connected to enclosure Mit Gehäuse verbunden Liaison au boîtier
Omgivelsestemperatur Ambient temperature Umgebungstemperatur Température ambiante Screened cable SI-Units (bar) 	-40 – 85 °C (-40 – 100 °C)				Skærm: Ikke forbundet til kapsling Screen: Not connected to enclosure Schirm: Nicht mit Gehäuse verbunden Blindage: Isolé du boîtier
Omgivelsestemperatur Ambient temperature Umgebungstemperatur Température ambiante Screened cable 	-30 – 85 °C				Skærm: Ikke forbundet til kapsling Screen: Not connected to enclosure Schirm: Nicht mit Gehäuse verbunden Blindage: Isolé du boîtier
Omgivelsestemperatur Ambient temperature Umgebungstemperatur Température ambiante AMP Econoseal 	-30 – 85 °C				
Omgivelsestemperatur Ambient temperature Umgebungstemperatur Température ambiante MetriPack 					Strømforsyning <15 W Power supply < 15 W Stromversorgung <15 W Alimentation <15 W 060G6552 - 060G6559, 060G6584, 060G6629, 060G7501-060G7509
Omgivelsestemperatur Ambient temperature Umgebungstemperatur Température ambiante EN6097-5-2, M12 x 1 	-40 – 85 °C (-25 – 90 °C)			-40 – 85 °C (-40 – 125 °C)	
Omgivelsestemperatur Ambient temperature Umgebungstemperatur Température ambiante	-40 – 85 °C (-25 – 90 °C)				

