

#### NT 65/2 Eco Me

The NT 65/2 Eco Me is a powerful, twin-engined wet/dry vacuum cleaner for professional applications. The flat pleated filter is cleaned efficiently by an air pulse system for almost constant suction power at all times.



#### 1 On-board storage

- The large on-board storage space on the casing head ensures that tools and accessories are always stored and close to hand.
- 2 Integrated drain hose (oil-resistant)
- Easily accessible drain hose for convenient liquid disposal.

# **TECHNICAL DATA AND EQUIPMENT**



#### NT 65/2 Eco Me

- Stainless steel container (Me)
- Power filter clean
- Drain hose (oil-resistant)

Technical data		
Order no.		1.325-151.0
EAN code		4039784046054
Air flow rate	I/s	2 x 56
Vacuum	mbar / kPa	235 / 23.5
Container capacity	1	65
Max. rated input power	W	max. 2760
Standard nominal width		40
Cable length	m	7.5
Sound pressure level	dB(A)	74
Container material		Metal
Number of motors		2
Frequency	Hz	50-60
Voltage	V	220-240
Weight	kg	22
Dimensions (L × W × H)	mm	740 × 560 × 890

Equipment					
Suction hose	m	4	Push handle		•
Suction Tube	piece(s) / m	2 × 0.5 / Metal	Safety class		II
Filter bag		Paper	Steering roller stop		1
Wet and dry floor nozzle	mm	360	Maintenance-free suction turbines	piece(s)	2
Crevice nozzle		•			
Automatic switch-off at max. filling quantity		•			
Eco filter system		•			
Stainless steel container					
Flat pleated filter		Paper			
Filter cleaning		Power filter clean			
Sturdy bumper		•			

■ Included in the scope of supply.























		Order no.	Quantity	ID	Length	Width	Price	Description	
Flat pleated filter, paper									H
Flat pleated filter, paper	1	6.904-283.0	1 piece(s)					Paper flat pleated filter (BIA-(U,S,G,C) dust class M) suitable for NT 65/2 Eco, NT 65/2 Eco Tc, NT 65/2 Eco Me.	-
Paper filter bags (two-ply)									
Paper filter bags	2	6.904-285.0	5 piece(s)					5 3-ply, tear-resistant paper filter bags. BIA-(U, S, G, C) dust class M. For all NT 48/1, NT 65/2 Eco + Me and NT 72/2 Eco Tc models.	
Bend, plastic						,			
Plastic bend	3	5.031-904.0	1 piece(s)	ID 40				Plastic bend (DN 40) with C-40 clip system, suitable for all NT models.	•
	4	5.031-718.0	1 piece(s)	ID 35				Plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models (except NT Eco M and NT Eco H).	
Bend, plastic, electrically conductive	5	5.031-939.0	1 piece(s)	ID 35				Electrically conductive plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models.	
	6	5.032-427.0	1 piece(s)	ID 40				Electrically conductive plastic bend (DN 40) with C-40 clip system, suitable for all NT vacuum cleaners.	
Floor nozzles									
DN 40 wet/dry floor nozzle	7	6.907-408.0	1 piece(s)	ID 40		360 mm		Multi-purpose nozzle (ID 40), plastic, 360 mm working width. With side rollers, brush strips (6.905-878.0) and squeegees (6.905-877.0).	-
Multi-purpose nozzle, wet/dry	8	6.903-018.0	1 piece(s)	ID 40		370 mm		All-purpose aluminium nozzle with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	
	9	6.906-383.0	1 piece(s)	ID 40		450 mm		All-purpose aluminium nozzle (DN 40) with 450 mm working width. With height-adjustable side rollers, brush strips (6.903-065.0) and oil-resistant squeegees (6.906-146.0). Only for NT vacuum cleaners.	
	10	6.906-384.0	1 piece(s)	ID 35		370 mm		All-purpose aluminium nozzle (DN 35) with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	
Crevice nozzles	1	1		1		ı			
Crevice nozzle	11	6.903-033.0	1 piece(s)	ID 40	290 mm			Plastic crevice tool (DN 40) for vacuuming in crevices and corners. Length: 290 mm.	-
	12	6.900-385.0	1 piece(s)	ID 35	210 mm			Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 210 mm.	
	13	6.900-922.0	1 piece(s)	ID 35	500 mm			Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 370 mm.	
	14	6.905-817.0	1 piece(s)	ID 40	400 mm			Metal crevice tool (DN 40) for vacuuming in crevices and corners. Length: 400 mm.	
Suction tubes, metal	1		L	L.D. 40	Loss			T-1	
Suction tube	15	6.900-275.0	1 piece(s)	ID 40	0.55 m			The suction tube (NW 40, 1 x 0.55 m) made from chrome-plated metal is standard in almost all commercial vacuum cleaners with twin motor. Optional for commercial single motor NT vacuum cleaner with suction hose NW 40.	•
	16	6.900-514.0	1 piece(s)	ID 35	0.5 m			Chromium-plated metal suction tube (DN 35, 1x0.5 m), standard for virtually all single-motor industrial NT vacuum	

<sup>■</sup> Included in the scope of supply. 

Available accessories.





























									$\top$
		Order no.	Quantity	ID	Length	Width	Price	Description	
Complete suction hoses (clip system	2)		1 ,					•	_
	1	1 4 4 4 0 6 7 0 0	1 ninco(s)	LID 40	1 4 m	I	I	4 m electrically non-conductive systion becomit bond	1
Suction hose + PFC module	17	4.440-679.0	1 piece(s)	ID 40	4 m			4 m electrically non-conductive suction hose with bend (C-DN 40) and module (4.060-474.0), bayonet at vacuum end and C 35 clip connection at accessory end.	•
Suction hose	18	4.440-678.0	1 piece(s)	ID 40	4 m			4 m electrically non-conductive suction hose with bend, bayonet at vacuum end and C 40 clip connection at accesso ry end. Without module.	- 0
Suction hose + PFC module, electri- cally conductive	19	4.440-728.0	1 piece(s)	ID 40	4 m			With bend and module (4.060-533.0), electrically conductive.	
Flat pleated filter, PES		I .	1					uvc.	_
Flat pleated filter, PES	20	6.904-284.0	1 piece(s)					Flat filter (PES) - BIA-(U,S,G,C) dust class M: rotproof polyes- ter fleece, ideal for wet use and abrasives. Standard for NT 72/2 Eco Tc.	
Fabric filter									
Membrane filter	21	6.904-282.0	1 piece(s)					Polyester needle fleece membrane/fabric filter - BIA-C -, washable up to 40°C, metal fibres for earthing. Suitable for virtually all industrial two-motor NT vacuum cleaners.	
HEPA, dust class H filter									
HEPA flat pleated filter	22	6.904-364.0	1 piece(s)					HEPA surface filter - dust class H (H 14) - with glass-fibre layers increases filter capacity when vacuuming health-endangering and carcinogenic dust.	
Plastic sacks for dust-free disposal									
Plastic sack for dust-free disposal	23	6.900-698.0	10 piece(s)					PE plastic sack.	
Wet filter bag				<u>'</u>	•				
Wet filter bag	24	6.904-252.0	5 piece(s)					Approved for dust class L, general cleaning, wet and dry, tear-resistant.	
Bends, stainless steel									
Bend, stainless steel, ID 35	25	6.903-141.0	1 piece(s)	ID 35				Stainless steel and crooked, ID 35	
Bend, stainless steel, ID 40	26	6.902-079.0	1 piece(s)	ID 40				Stainless steel and crooked, ID 40	
Bends, metal									
Bend, metal	27	6.900-519.0	1 piece(s)	ID 35				Robust, chromium-plated metal bend (DN 35), can be used instead of a plastic bend (with clip system adapter 5.407-112.0; C 35-DN 35, plastic, el.).	
	28	6.900-276.0	1 piece(s)	ID 40				Robust, chromium-plated metal bend (DN 40), can be used instead of a plastic bend (with clip system adapter 5.407-111.0; C 40-DN 40, plastic, el.).	
Car cleaning nozzles									
Car nozzle	29	6.900-952.0	1 piece(s)	ID 40		90 mm		Angled, flat, plastic car vacuuming tool with about 90 mm working width. Only for NT vacuum cleaners.	
Rubber suction tools, nose 45°		1	_						
Rubber suction tool, nose 45°	30	6.902-104.0	1 piece(s)	ID 35	220 mm			45° rubber suction nozzle (DN 35), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	
	31	6.902-105.0	1 piece(s)	ID 40	220 mm			45° rubber suction nozzle (DN 40), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	;   _
Pipe dusting nozzles								To vaccoming machines, only for 141 vaccom clediters.	
Pipe brush 35/100	32	6.903-035.0	1 piece(s)	ID 35				Plastic, pipe diameter 100 mm	
Pipe brush 35/200	33	6.903-036.0	1 piece(s)	ID 35				Plastic, pipe diameter 100 mm	
	33	1 0.303 030.0	1 picce(s)	110 33				Trastic, pipe didirector 200 milli	14
Suction brushes Suction brush	34	6.903-862.0	1 piece(s)	ID 35		70 mm		Rotatable suction brush (DN 35) with natural bristles (cow hair). Bristle size 70x45 mm. Only CV and NT vacuum clean ers.	- 0
			1					1 6.5.	

<sup>■</sup> Included in the scope of supply. 

Available accessories.































									_
		Order no.	Quantity	ID	Length	Width	Price	Description	
Suction tubes, stainless steel		I.							
Suction tube	35	6.902-081.0	1 piece(s)	ID 40	0.5 m			Stainless steel suction tube (DN 40, 0.5 m) only suitable for	П
								NT vacuum cleaners.	
	36	6.906-531.0	1 piece(s)	ID 40	1 m			Stainless steel suction tube (DN 40, 1.0 m) only suitable for NT vacuum cleaners.	
Repair kits								WY Vacoun cicaners.	_
Repair kit, C 40	37	2.639-873.0	1 piece(s)	ID 40				Repair set (C40) includes threaded hose adapters (without	
								bayonet adapter) for industrial NT vacuum cleaners with cli	р□
								system.	-
Repair kit, ID 61	38	2.862-038.0	1 piece(s)	ID 61				Suction hose repair kit. Optional for all NT 65/2 and 72/2, NT 993 I, NT 802 I.	
Suction hoses (clip system)		l						I 303 I, NI 602 I.	_
Suction hose	39	6.906-279.0	1 piece(s)	40	10 m			10 m standard suction hose without bend and adapter. With	ı
								bayonet at vacuum end and C 40 clip connection at accesso	- 🗆
								ry end.	-
	40	6.906-321.0	1 piece(s)	40	4 m			4 m suction hose with bayonet and C 40 clip connection. Without bend and adapter.	
	41	6.906-714.0	1 piece(s)	40	4 m			With bayonet and clip connection.	
	42	6.906-546.0	1 piece(s)	40	4 m			Electrically conductive, 4 m suction hose with bayonet and	_
								40 clip connection. Without bend and adapter.	
	43	6.906-635.0	1 piece(s)	40	16 m			With bayonet and clip connection.	
	44	6.906-877.0	1 piece(s)	40	10 m			Suction hose with bayonet coupling, electrically conductive.	
Suction hoses complete		I	1	1	1.	ı		1	
Suction hose, complete	45	4.440-264.0	1 piece(s)	ID 61	4 m			4-m standard suction hose with DN 61 bayonet connector at the device end and DN 61 tapered connector at the accessor	
								ry end.	-
	46	4.440-467.0	1 piece(s)	ID 61	10 m			10-m standard suction hose with DN 61 bayonet connector	
								at the device end and DN 61 tapered connector at the ac-	
Custian has complete all regist	47	4.440-613.0	1 = 1 = 1 = 1	ID 61	4 m			cessory end.	+
Suction hose, complete, oil-resist- ant	47	4.440-613.0	1 piece(s)	ID 01	4 111			Oil-resistant.	
Suction hose, complete, electrically	48	4.440-616.0	1 piece(s)	ID 61	4 m			Electrically conductive.	
conductive									╚
Connecting sleeves	1	l	1	1				1	
Adapter, ID 32/35, with internal thread	49	6.902-077.0	1 piece(s)	ID 32				Electrically non-conductive adapter with internal thread. For connecting two suction hoses without connectors. Suitable	r
tilleau								for DN 32 or DN 35.	"
Connecting adapter, ID 40, with	50	6.900-286.0	1 piece(s)	ID 40				Electrically non-conductive adapter with screw thread at	
internal thread								both ends. For connecting 2 DN 40 suction hoses without	
Connection alone ID C4 with		6 000 070 0	4 -:(-)	ID C4				connectors.	+
Connecting sleeve, ID 61, with female thread	51	6.902-078.0	1 piece(s)	ID 61				For connecting 2 suction hoses, thread on both sides	
Extension hoses (clip system)		II.							
Extension hose	52	6.906-344.0	1 piece(s)	ID 40	2.5 m			2.5 m electrically non-conductive standard extension hose	l_
							<u> </u>	for all C-40 hoses with clip system.	╚
Y-adapter kit	1	1	1	1		1	1	Language and the second	
Y-adapter kit		2.637-217.0	1 piece(s)	ID 35				Plastic distributor - suitable for NT vacuum cleaners.	
Connection adapter C ID (clip to con Connection adapter C DN 35	1	5.407-112.0	1 piece(s)	ID 35		I		C 35 hose connector for DN 35 accessory, electrically con-	
Connection adapter C DN 33	54	J.4U/-112.U	T hiere(2)	רכ טו				ductive.	































		Order no.	Quantity	ID	Length	Width	Price	Description	
Connection adapter C DN 40	55	5.407-109.0	1 piece(s)	ID 40				Electrically conductive adapter (C 40) with DN 35 connection for connecting DN 35 accessories to an industrial C 40	
		5 407 444 0	4 -:(-)	ID 40				or C-DN 40 suction hose. Suitable for NT vacuum cleaners.	+
	56	5.407-111.0	1 piece(s)	ID 40				C 40 hose connector for DN 40 accessory, electrically conductive.	
Connection adapter for power tools			onductive						
Connection adapter for power tools, C 35, electrically conductive	57	5.453-042.0	1 piece(s)	ID 35				3-way plastic adapter. For DN 26 to DN 36. For connecting power tools to an industrial C or C-DN 35 suction hose. Suitable for NT vacuum cleaners.	
	58	5.453-048.0	1 piece(s)	ID 35				Inside Ø 25.4 mm, outside Ø 34.6 mm/ 38 mm, electrically conductive. Only NT vacuums.	
Connection Adaptor for power tools, C 35, electrically conductive	59	5.453-049.0	1 piece(s)	ID 35				Inner Ø 28.6 mm, outer Ø 37.3 mm/ 38.8 mm, el. Only NT-vacuums.	
Connection adapter for power tools, C 35, electrically conductive	60		1 piece(s)	ID 35				Inside Ø 27 mm, outside Ø 36.5 mm/38.8 mm, electrically conductive. Only NT vacuums.	
Connection Adaptor for power		5.453-051.0	1 piece(s)	ID 35				Inner Ø 32 mm, outer Ø 39 mm, el. Only NT-vacuums.	
tools, C 35, electrically conductive		5.453-052.0	1 piece(s)	ID 35				Inner Ø 28 mm, outer Ø 34 mm/ 38.8 mm, el. Only NT-vacu ums.	)- [
Adapter for electric power tools, scr			l	Libras	ı	1	ı	la	П
Adapter for electric power tools, screwable, ID 35		5.453-016.0	1 piece(s)	ID 35				3-way plastic adapter with fitting instructions. For DN 26 to DN 36. For connecting to an industrial DN 35 suction hose.	L
	64		1 piece(s)	ID 35				Inside Ø 28.6 mm, outside Ø 37.3/38.8 mm.	]
	65	6.902-059.0	1 piece(s)	ID 35				Electrically conductive power tool adapter, threaded. Internal diameter: 32 mm.External diameter: 39 mm.	
	66	6.902-095.0	1 piece(s)	ID 35				2-way power tool adapter, threaded. For connecting to an industrial DN 35 suction hose. Internal diameter: 28 mm. External diameter: 34 mm and 38.8 mmSuitable for NT vacuum cleaners.	
Expansion pieces (tube -> nozzle)					l l	1	1	vacosiii cicariors.	Ė
Adapter	67	5.453-019.0	1 piece(s)	ID 40				From DN 40 to DN 61: Plastic adapter (electrically non-conductive). Suitable for NT vacuum cleaners.	- [
Reducing sleeves			,						
Reducer	68	5.407-108.0	1 piece(s)	ID 40				Threaded reducer - from C-40 to DN 35. Suitable for NT vacuum cleaners.	[
Reduction bushing	69	5.407-113.0	1 piece(s)	ID 40				Reducer (C 40 to C 35) for connecting accessories with C-35 clip connection to suction hoses with C 40 clip system.	ع دَ
Reducers (tube -> nozzle)		l	L	L.D. 40		I	ı	la company of the com	
Reducer	70	6.902-017.0	1 piece(s)	ID 40				Reducer for accessory extension. Ideal for accessories with DN 35 connecting cone in combination with accessories wit DN 40 connecting cone.	
Reducer from ID 35 to ID 32	71	6.902-072.0	1 piece(s)	ID 35				Reducer with internal connecting cone DN 32. Ideal for accessories from the industrial vacuum cleaner range in combination with industrial NT vacuum cleaners.	
Reduction/expansion adapter kit			1						
Set of reducers / adapter sleeves		2.860-117.0	1 piece(s)					DN 40/35, DN 35/32 (tube -> nozzle), plastic.	]
Target-group-specific accessory kits				1			1	1	4
Professional cleaning kit	73	2.637-353.0		ID 40				Individual parts: Suction hose 4 m (4.440-263.0), bend, metal (6.900-276.0), suction tube 2 x 0.5 m, metal (6.900-275.0), grout nozzle (6.903-033.0), floor nozzle with rollers (6.903-051.0).	s [
Modification kit, non-conductive me	edia								Ė
		2.640-426.0	1 piece(s)					For switching off when vacuuming non-conductive fluids.	H





		Order no.	Length	Colour	Quanti- ty	Price	Description
Miscellaneous	· ·						
Extension cable	1	6.647-022.0	20 m		1 piece(s)		Extension cable, 20 m, 3x1.5 mm <sup>2</sup> . With splash-proof earthing pin plug, strain relief and anti-kink sleeve.

 $<sup>\</sup>blacksquare$  Included in the scope of supply.  $\hfill\Box$  Available accessories.

Contact: +971507924960

Email: sales@industrytechstore.com Website: www.lndustrytechstore.com