



circuit breaker Easypact EZC100F - TMD - 16A - 3 poles 3d

EZC100F3016

! To be discontinued on: 1 Dec 2024

! To be discontinued

Main

Range of product	EasyPact	
Product or component type	Circuit breaker	
Device short name	Easypact EZC100F	
Circuit breaker name	Easypact EZC100F	
Device application	Distribution	
Poles description	3P	
Protected poles description	3t	
Network type	AC	
	DC	
Network frequency	50/60 Hz	
[In] rated current	16 A at 40 °C	
[Ui] rated insulation voltage	age 690 V AC 50/60 Hz conforming to IEC 60947-2	
[Uimp] rated impulse withstand voltage	e withstand 6 kV conforming to IEC 60947-2	
[Ue] rated operational voltage	550 V AC 50/60 Hz conforming to IEC 60947-2 250 V DC conforming to IEC 60947-2	
Breaking capacity code	F	
Breaking capacity	25 kA Icu at 220240 V AC 50/60 Hz conforming to IEC 60947-2 5 kA Icu at 125 V DC 1P conforming to IEC 60947-2 5 kA Icu at 250 V DC 2P conforming to IEC 60947-2 5 kA Icu at 550 V AC 50/60 Hz conforming to IEC 60947-2 7.5 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 10 kA Icu at 380415 V AC 50/60 Hz conforming to IEC 60947-2	
[Ics] rated service breaking capacity	2.5 kA at 125 V DC conforming to IEC 60947-2 2.5 kA at 250 V DC conforming to IEC 60947-2 2.5 kA at 550 V AC 50/60 Hz conforming to IEC 60947-2 3.75 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 5 kA at 380415 V AC 50/60 Hz conforming to IEC 60947-2 12.5 kA at 220240 V AC 50/60 Hz conforming to IEC 60947-2	
Suitability for isolation	Yes conforming to IEC 60947-2	
Utilisation category	Category A	
Trip unit name	TM-D	
Trip unit technology	Thermal-magnetic	
Trip unit rating	16 A at 50 °C	
Protection type	Overload protection	
. .	Short-circuit protection	
Pollution degree	3 conforming to IEC 60947	

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Complementary

,		
Control type	Toggle	
Mounting mode	Fixed	
Mounting support	Backplate	
Upside connection	Front	
Downside connection	Front	
Mechanical durability	13000 cycles	
Electrical durability	Category A: 4000 cycles 415 V AC 50/60 Hz conforming to IEC 60947-2	
Connection pitch	25 mm	
Local signalling	Positive contact indication	
Neutral protection setting	Without protection	
Earth-leakage protection	Without	
Height	130 mm	
Width	75 mm	
Depth	60 mm	

Environment

Standards	EN/IEC 60947-1 JIS C8201-2-2 GB/T 14048.2 EN/IEC 60947-2	
IP degree of protection	IP20 conforming to IEC 60529	
IK degree of protection	IK07 conforming to EN 50102	
Ambient air temperature for operation	-2570 °C	
Ambient air temperature for storage	-3585 °C	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.5 cm
Package 1 Width	14.0 cm
Package 1 Length	8.0 cm
Package 1 Weight	792.0 g

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh


Well-being performance

	Toxic Heavy Metal Free	
②	Mercury Free	
⊘	Rohs Exemption Information	Yes


Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations


Dimensions Drawings



Assembly



Performance Curves



Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features



Contact: +971507924960

Email: sales@industrytechstore.com

