

control unit Micrologic 2.0 A, basic protections LI, ammeter measurement

33071

Main

Product or component type	Control unit
Trip unit name	MicroLogic 2.0 A
Trip unit technology	Electronic
Range compatibility	MasterPact NT
	MasterPact NW
	Compact NS
	Masterpact MT
device application	Distribution
Number of poles	4P
	3P
Protected poles description	4t
	3t
	3t + N/2
Trip unit protection functions	Basic protection
Protection type	for overload protection (long time)
	for instantaneous short-circuit protection
Trip unit rating	630 A at 50 °C
	800 A at 50 °C
	1000 A at 50 °C
	1250 A at 50 °C
	1600 A at 50 °C
	2000 A at 50 °C
	2500 A at 50 °C
	3200 A at 50 °C
	4000 A at 50 °C
	5000 A at 50 °C
	6300 A at 50 °C
Network type	AC
Network frequency	50/60 Hz
Circuit breaker mounting mode	Fixed
	Drawout

Complementary

Long-time pick-up adjustment type Ir (thermal protection)	Adjustable 9 settings
[Ir] long-time protection pick-up adjustment range	0.41 x ln
Long-time protection delay adjustment type tr	Adjustable 9 settings
[tr] long-time protection delay adjustment range	0.716.6 s at 7.2 x lr 0.724 s at 6 x lr 12.5600 s at 1.5 x lr
Thermal memory	20 mn

Instantaneous protection pick-up adjustment type li	Adjustable 9 settings
[li] instantaneous protection pick- up adjustment range	1.510 x lr
Earth-leakage protection	Without
Zone selective interlocking ZSI	Without
Local signalling	3 LEDs (red) for electrical fault 1 LED (red) for internal error
Display type	Digital display
Type of measurement	Ammeter
Communication of data	Measurement readout Protection and alarm settings

Environment

Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-4085 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.800 cm
Package 1 Width	8.000 cm
Package 1 Length	21.500 cm
Package 1 Weight	247.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	15
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	4.150 kg
Unit Type of Package 3	P12
Number of Units in Package 3	120
Package 3 Height	50.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	45.416 kg

Contractual warranty

Warranty	18 months
----------	-----------



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contact: +971507924960

Email: sales@industrytechstore.com

